

Boeing BMS 5-28, Type 18, Class 1.

\* Based on internal testing

# Epocast® 1648 A/B

### Adhesive and void filler







#### **Features**

- > Low density of 0.68 g/cm<sup>3</sup>
- > High compressive strength of 7,250 psi or 50 MPa
- > Fast setting (gel time 60 g = 18 min)
- > Meets FST requirements
- > Can be dispensed by meter mix machines
- > Contains no SVHC under REACH

#### **Benefits**

- > Weight savings
- > Utilization in higher load applications
- > Improved productivity/greater throughput
- > Manufacturing versatility
- > Global availability

## **Packaging**

Available in cartridges and bulk packaging

Learn more at www.aralditeadhesives.com

For any other information, please send an e-mail to advanced\_materials@huntsman.com

Europe +41 61 299 20 41 India, Middle East, Africa & Turkey + 91 22 4095 1556 Asia / Pacific + 86 21 2208 7588 Americas +1 888 564 9318





Legal information All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof in one or more, but not all, countries. Sales of the product described herein ("Product") are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials (Europe) BV