



# SAFETY DATA SHEET

## SPECIALTY ELECTRONIC MATERIALS UK LIMITED

Safety Data Sheet according to Reg. (EU) No 2015/830

**Product name: MOLYKOTE™ D-321 R Anti-Friction Coating**

**Revision Date:** 17.10.2018

**Version:** 7.0

**Date of last issue:** 16.10.2017

**Print Date:** 21.02.2020

SPECIALTY ELECTRONIC MATERIALS UK LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

**Product name:** MOLYKOTE™ D-321 R Anti-Friction Coating

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricants and lubricant additives

### 1.3 Details of the supplier of the safety data sheet

#### COMPANY IDENTIFICATION

SPECIALTY ELECTRONIC MATERIALS UK  
LIMITED  
STATION ROAD, BIRCH VALE, HIGH PEAK  
DERBYSHIRE  
England  
SK22 1BR  
UNITED KINGDOM

**Customer Information Number:**

800-3876-6838

SDSQuestion-EU@dupont.com

### 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** +(44)-870-8200418

**Local Emergency Contact:** +(44)-870-8200418

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008:

Flammable liquids - Category 3 - H226

Eye irritation - Category 2 - H319

Specific target organ toxicity - single exposure - Category 3 - H336

Specific target organ toxicity - repeated exposure - Category 1 - H372

Aspiration hazard - Category 1 - H304

Chronic aquatic toxicity - Category 2 - H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

### Hazard pictograms



Signal word: DANGER

### Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P273	Avoid release to the environment.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

**Contains** n-Butyl acetate; Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha; 1-Butanol

## 2.3 Other hazards

Static-accumulating flammable liquid.

---

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

---

**Chemical nature:** Inorganic and organic compounds, in mineral oil

## 3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
<b>CASRN</b> 64742-82-1 <b>EC-No.</b> 265-185-4 <b>Index-No.</b> 649-330-00-2	—	>= 30.0 - <= 32.0 %	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha	Flam. Liq. - 3 - H226 STOT SE - 3 - H336 STOT RE - 1 - H372 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411
<b>CASRN</b> 9022-96-2 <b>EC-No.</b> Polymer <b>Index-No.</b> —	—	>= 10.0 - <= 11.0 %	Polybutyl titanate	Flam. Liq. - 3 - H226 Eye Irrit. - 2 - H319
<b>CASRN</b> 71-36-3 <b>EC-No.</b> 200-751-6 <b>Index-No.</b> 603-004-00-6	01-2119484630-38	>= 1.0 - <= 1.1 %	1-Butanol	Flam. Liq. - 3 - H226 Acute Tox. - 4 - H302 Skin Irrit. - 2 - H315 Eye Dam. - 1 - H318 STOT SE - 3 - H336 STOT SE - 3 - H335
<b>CASRN</b> 1314-13-2 <b>EC-No.</b> 215-222-5 <b>Index-No.</b> 030-013-00-7	01-2119463881-32	>= 0.55 - <= 0.65 %	Zinc oxide	Aquatic Acute - 1 - H400 Aquatic Chronic - 1 - H410
Substances with a workplace exposure limit				
<b>CASRN</b> 123-86-4 <b>EC-No.</b> 204-658-1 <b>Index-No.</b> 607-025-00-1	01-2119485493-29	>= 33.0 - <= 34.0 %	n-Butyl acetate	Flam. Liq. - 3 - H226 STOT SE - 3 - H336
<b>CASRN</b> 1317-33-5 <b>EC-No.</b> 215-263-9 <b>Index-No.</b> —	—	>= 18.0 - <= 19.0 %	Molybdenum disulfide	Not classified

<b>CASRN</b> 7782-42-5 <b>EC-No.</b> 231-955-3 <b>Index-No.</b> —	01-2119486977-12	>= 4.0 - <= 5.0 %	Graphite	Not classified
--	------------------	-------------------	----------	----------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: FIRST AID MEASURES

---

### 4.1 Description of first aid measures

#### General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**4.2 Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

---

## SECTION 5: FIREFIGHTING MEASURES

---

### 5.1 Extinguishing media

**Suitable extinguishing media:** Water spray Alcohol-resistant foam Carbon dioxide (CO<sub>2</sub>) Dry chemical

**Unsuitable extinguishing media:** High volume water jet Do not use direct water stream.

### 5.2 Special hazards arising from the substance or mixture

**Hazardous combustion products:** Carbon oxides Sulphur oxides

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Vapours may form explosive mixtures with air.

### 5.3 Advice for firefighters

**Fire Fighting Procedures:** Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

## SECTION 6: ACCIDENTAL RELEASE MEASURES

---

**6.1 Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

**6.2 Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**6.3 Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Clean up remaining materials from spill with suitable absorbent. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**6.4 Reference to other sections:**

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: HANDLING AND STORAGE

---

**7.1 Precautions for safe handling:** Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases.

**7.3 Specific end use(s):** See the technical data sheet on this product for further information.

---

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
1-Butanol	ACGIH	TWA	20 ppm
	GB EH40	STEL	SKIN
	GB EH40	STEL	154 mg/m <sup>3</sup> 50 ppm
Zinc oxide	ACGIH	TWA Respirable fraction	2 mg/m <sup>3</sup>
	ACGIH	STEL Respirable fraction	10 mg/m <sup>3</sup>
n-Butyl acetate	ACGIH	TWA	50 ppm
	ACGIH	STEL	150 ppm
	Dow IHG	TWA	75 ppm
	Dow IHG	STEL	150 ppm
	GB EH40	TWA	724 mg/m <sup>3</sup> 150 ppm
	GB EH40	STEL	966 mg/m <sup>3</sup> 200 ppm

Molybdenum disulfide	ACGIH	TWA Inhalable fraction	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable fraction	3 mg/m3 , Molybdenum
	GB EH40	TWA	10 mg/m3 , Molybdenum
	GB EH40	STEL	20 mg/m3 , Molybdenum
Graphite	ACGIH	TWA Respirable fraction	2 mg/m3
	GB EH40	TWA inhalable dust	10 mg/m3
	GB EH40	TWA Respirable dust	4 mg/m3

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:  
butanol

**Derived No Effect Level**

Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	570 mg/m3	n.a.	330 mg/m3	44 mg/kg bw/day	330 mg/m3	n.a.	n.a.

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	570 mg/m3	n.a.	n.a.	n.a.	26 mg/kg bw/day	71 mg/m3	26 mg/kg bw/day	n.a.	n.a.

**1-Butanol**

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	310 mg/m3

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	3.125 mg/kg bw/day	n.a.	55 mg/m3

Zinc oxide

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	83 mg/kg bw/day	5 mg/m3	n.a.	n.a.

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	83 mg/kg bw/day	2.5 mg/m3	0.83 mg/kg bw/day	n.a.	n.a.

n-Butyl acetate

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	600 mg/m3	11 mg/kg bw/day	600 mg/m3	11 mg/kg bw/day	300 mg/m3	n.a.	300 mg/m3

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
6 mg/kg bw/day	300 mg/m3	2 mg/kg bw/day	n.a.	300 mg/m3	6 mg/kg bw/day	35.7 mg/m3	2 mg/kg bw/day	n.a.	35.7 mg/m3

Graphite

**Workers**

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	1.2 mg/m3

**Consumers**

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	813 mg/kg bw/day	n.a.	0.3 mg/m3

**Predicted No Effect Concentration**

1-Butanol

Compartment	PNEC
Fresh water	0.082 mg/l
Marine water	0.008 mg/l
Intermittent use/release	2.25 mg/l
Sewage treatment plant	2476 mg/l
Fresh water sediment	0.178 mg/kg
Marine sediment	0.018 mg/kg
Soil	0.015 mg/kg

Zinc oxide

Compartment	PNEC
Fresh water	20.6 µg/l
Marine water	6.1 µg/l
Sewage treatment plant	52 µg/l
Fresh water sediment	117.8 mg/kg
Marine sediment	56.5 mg/kg
Soil	35.6 mg/kg

n-Butyl acetate

Compartment	PNEC
Fresh water	0.18 mg/l
Marine water	0.018 mg/l
Intermittent use/release	0.36 mg/l
Fresh water sediment	0.981 mg/kg dry weight (d.w.)
Marine sediment	0.0981 mg/kg dry weight (d.w.)
Soil	0.09 mg/kg dry weight (d.w.)
Sewage treatment plant	35.6 mg/l

## 8.2 Exposure controls

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

### Individual protection measures

**Eye/face protection:** Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

#### Skin protection

**Hand protection:** Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according

to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

### Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	dark grey
Odor	solvent-like
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 100 °C
Flash point	closed cup 23 °C

Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.07
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Kinematic Viscosity	< 20.5 mm <sup>2</sup> /s at 25 °C
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

#### 9.2 Other information

Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## SECTION 10: STABILITY AND REACTIVITY

---

**10.1 Reactivity:** Not classified as a reactivity hazard.

**10.2 Chemical stability:** Stable under normal conditions.

**10.3 Possibility of hazardous reactions:** Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Flammable liquid and vapour.

**10.4 Conditions to avoid:** Heat, flames and sparks.

**10.5 Incompatible materials:** Oxidizing agents

**10.6 Hazardous decomposition products:** Butanol.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

## 11.1 Information on toxicological effects

### Acute toxicity

#### Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 5,000 mg/kg Estimated.

#### Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 5,000 mg/kg Estimated.

#### Acute inhalation toxicity

Prolonged excessive exposure may cause adverse effects. May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may cause irritation to upper respiratory tract (nose and throat).

As product: The LC50 has not been determined.

### Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Prolonged contact may cause skin irritation with local redness.

May cause drying and flaking of the skin.

### Serious eye damage/eye irritation

May cause severe eye irritation.

May cause corneal injury.

### Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

### Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

### Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in humans:  
Central nervous system.

Contains component(s) which have been reported to cause effects on the following organs in animals:  
Nasal tissue.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Contains component(s) which caused birth defects in laboratory animals only at doses toxic to the mother. Contains component(s) which, in laboratory animals, have been toxic to the fetus only at doses toxic to the mother.

**Reproductive toxicity**

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals. Contains component(s) which did not interfere with fertility in animal studies.

**Mutagenicity**

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

**Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, resulting in rapid absorption and injury to other body systems.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

**Acute inhalation toxicity**

Based on data from similar materials LC50, Rat, 4 Hour, vapour, > 13.1 mg/l

**Polybutyl titanate**

**Acute inhalation toxicity**

The LC50 has not been determined.

**1-Butanol**

**Acute inhalation toxicity**

LC50, Rat, male and female, 4 Hour, vapour, > 17.76 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

**Zinc oxide**

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 5 mg/l No deaths occurred at this concentration.

**n-Butyl acetate**

**Acute inhalation toxicity**

The LC50 has not been determined.

**Molybdenum disulfide**

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

**Graphite**

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 2 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

*Ecotoxicological information appears in this section when such data is available.*

### 12.1 Toxicity

#### **Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

##### **Acute toxicity to fish**

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

Based on data from similar materials

LL50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 10 - 30 mg/l, OECD Test Guideline 203

##### **Acute toxicity to aquatic invertebrates**

Based on data from similar materials

EL50, Daphnia magna (Water flea), 48 Hour, 10 - 22 mg/l, OECD Test Guideline 202

##### **Acute toxicity to algae/aquatic plants**

Based on data from similar materials

EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 4.6 - 10 mg/l, OECD Test Guideline 201

Based on data from similar materials

NOELR, Pseudokirchneriella subcapitata (green algae), 72 Hour, 0.22 mg/l, OECD Test Guideline 201

##### **Chronic toxicity to aquatic invertebrates**

Based on data from similar materials

NOELR, Daphnia magna (Water flea), 21 d, 0.097 mg/l

#### **Polybutyl titanate**

##### **Acute toxicity to fish**

Not expected to be acutely toxic to aquatic organisms.

#### **1-Butanol**

##### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 1,376 mg/l, OECD Test Guideline 203 or Equivalent

##### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1,328 mg/l, OECD Test Guideline 202 or Equivalent

##### **Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 225 mg/l, OECD Test Guideline 201 or Equivalent

**Toxicity to bacteria**

EC50, Pseudomonas putida, static test, 17 Hour, Growth inhibition, > 1,000 mg/l, DIN 38412

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 4.1 mg/l

**Toxicity to Above Ground Organisms**

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

**Zinc oxide**

**Acute toxicity to fish**

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 0.14 - 1.1 mg/l

LC50, Danio rerio (zebra fish), 96 Hour, 1 - 10 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 1 - 10 mg/l

**Acute toxicity to algae/aquatic plants**

IC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, 0.136 mg/l

**Toxicity to bacteria**

Based on data from similar materials

EC50, 3 Hour, 5.2 mg/l, OECD Test Guideline 209

**Chronic toxicity to fish**

NOEC, Danio rerio (zebra fish), 32 d, mortality, >= 0.540 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.04 mg/l

**n-Butyl acetate**

**Acute toxicity to fish**

Material is harmful to aquatic organisms (LC50/EC50/IC50 between 10 and 100 mg/L in the most sensitive species).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 18 mg/l

**Acute toxicity to aquatic invertebrates**

LC50, Daphnia magna (Water flea), 48 Hour, 44 mg/l, Method Not Specified.

**Acute toxicity to algae/aquatic plants**

ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 648 mg/l

**Toxicity to bacteria**

EC50, Bacteria, 16 Hour, > 1,000 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, 23 mg/l

### **Molybdenum disulfide**

#### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

For similar material(s):

LC50, Fish, 96 Hour, > 100 mg/l

#### **Acute toxicity to aquatic invertebrates**

Based on data from similar materials

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

#### **Acute toxicity to algae/aquatic plants**

Based on data from similar materials

ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

#### **Toxicity to bacteria**

EC50, 30 Hour, Respiration rates., > 100 mg/l

#### **Chronic toxicity to fish**

Based on data from similar materials

NOEC, Fish, 34 d, > 10 mg/l

#### **Chronic toxicity to aquatic invertebrates**

Based on data from similar materials

NOEC, Daphnia magna, 21 d, > 10 mg/l

### **Graphite**

#### **Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

#### **Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

#### **Toxicity to bacteria**

EC50, 3 Hour, > 1,012.5 mg/l, OECD Test Guideline 209

## **12.2 Persistence and degradability**

### **Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Based on data from similar materials 10-day Window: Pass

**Biodegradation:** 74.7 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F

**Polybutyl titanate**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

**1-Butanol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 98 %

**Exposure time:** 19 d

**Method:** OECD Test Guideline 301E or Equivalent

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	68 %
10 d	87 %
15 d	92 %
20 d	92 %

**Zinc oxide**

**Biodegradability:** Biodegradation is not applicable.

**n-Butyl acetate**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 83 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301D or Equivalent

**Molybdenum disulfide**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

**Graphite**

**Biodegradability:** Biodegradation is not applicable.

**12.3 Bioaccumulative potential**

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

**Bioaccumulation:** Based on data from similar materials

**Partition coefficient: n-octanol/water(log Pow):** > 4

**Polybutyl titanate**

**Bioaccumulation:** No relevant data found.

**1-Butanol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 1 at 25 °C OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

**Bioconcentration factor (BCF):** 3.16 Fish Estimated.

**Zinc oxide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**Bioconcentration factor (BCF):** 177 Fish

**n-Butyl acetate**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** Pow: 3.2 at 25 °C Measured

**Bioconcentration factor (BCF):** 15 Fish Estimated.

**Molybdenum disulfide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**Graphite**

**Bioaccumulation:** No relevant data found.

**12.4 Mobility in soil****Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

No relevant data found.

**Polybutyl titanate**

No relevant data found.

**1-Butanol**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 2.4 Estimated.

**Zinc oxide**

No data available.

**n-Butyl acetate**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 19 - 70 Estimated.

**Molybdenum disulfide**

No relevant data found.

**Graphite**

No relevant data found.

**12.5 Results of PBT and vPvB assessment****Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**Polybutyl titanate**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**1-Butanol**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**Zinc oxide**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**n-Butyl acetate**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**Molybdenum disulfide**

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

**Graphite**

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

**12.6 Other adverse effects****Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Polybutyl titanate**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**1-Butanol**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Zinc oxide**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**n-Butyl acetate**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Molybdenum disulfide**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Graphite**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national

and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

---

## SECTION 14: TRANSPORT INFORMATION

---

### Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number	UN 1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
14.3 Transport hazard class(es)	3
14.4 Packing group	III
14.5 Environmental hazards	Naphtha (petroleum), hydrodesulfurized heavy, Zinc oxide
14.6 Special precautions for user	Hazard Identification Number: 30

### Classification for SEA transport (IMO-IMDG):

14.1 UN number	UN 1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
14.3 Transport hazard class(es)	3
14.4 Packing group	III
14.5 Environmental hazards	Naphtha (petroleum), hydrodesulfurized heavy, Zinc oxide
14.6 Special precautions for user	EmS: F-E, S-E
14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

### Classification for AIR transport (IATA/ICAO):

14.1 UN number	UN 1993
14.2 UN proper shipping name	Flammable liquid, n.o.s.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
14.3 Transport hazard class(es)	3
14.4 Packing group	III
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

## SECTION 15: REGULATORY INFORMATION

---

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### REACH Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH). Polymers are exempted from registration under REACH. All relevant starting materials and additives have been either pre-registered, registered, or are exempt from registration to Regulation (EC) No. 1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

#### Restrictions on the manufacture, placing on the market and use:

The following substance/s contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product have to comply with the restrictions placed upon it by the aforementioned provision.

CAS-No.: 64742-82-1	Name: Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha
---------------------	--

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

#### Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5,000 t

50,000 t

Listed in Regulation: ENVIRONMENTAL HAZARDS

Number in Regulation: E2

200 t

500 t

Listed in Regulation: Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Number in Regulation: 34

2,500 t

25,000 t

### Further information

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

Not applicable

---

## SECTION 16: OTHER INFORMATION

---

### Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Flam. Liq. - 3 - H226 - Based on product data or assessment  
 Eye Irrit. - 2 - H319 - Calculation method  
 STOT SE - 3 - H336 - Calculation method  
 STOT RE - 1 - H372 - Calculation method  
 Asp. Tox. - 1 - H304 - Based on product data or assessment  
 Aquatic Chronic - 2 - H411 - Calculation method

### Revision

Identification Number: 2287978 / A670 / Issue Date: 17.10.2018 / Version: 7.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

### Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
GB EH40	UK. EH40 WEL - Workplace Exposure Limits
SKIN	Absorbed via skin
STEL	Short-term exposure limit
TWA	8-hour, time-weighted average

Acute Tox.	Acute toxicity
Aquatic Acute	Acute aquatic toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure

### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

SPECIALTY ELECTRONIC MATERIALS UK LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become

aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

GB