18, ZI Haneboesch L-4562 Differdange I UXFMBOURG Phone: +352 58 22 82 1 Fax: +352 58 49 35 E-mail: sales@airtech.lu Website: www.airtech.lu

Data Sheet

INFUSION TUBING CONNECTORS & VALVES

Infusion tube fittings

DESCRIPTION

Various infusion tube fittings are available to connect tubes and valves to control resin flow.

TECHNICAL DATA

Nylon fittings

Material type Nylon
Maximum use temperature 180°C
Colour Translucent


Infusion valve

Material type Polypropylene

Maximum use temperature 121°C Colour Black

SIZES

Connector type	Part Name	Works with:
Nylon barb "T" fittings	NTF38	3/8" I.D. tubing
	NTF12	1/2" I.D. tubing
	NTF58	5/8" I.D. tubing
Nylon barb elbow fittings	NEF38	3/8" I.D. tubing
	NEF12	1/2" I.D. tubing
	NEF58	5/8" I.D. tubing
Nylon barb coupling fittings	NCF38	3/8" I.D. tubing
	NCF12	1/2" I.D. tubing
	NCF58	5/8" I.D. tubing
Infusion Valve	InfuValve	3/8" I.D. tubing



NOTES

• The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated: 2021-03-23

Catalogue position: Resin infusion products