

# SAFETY DATA SHEET Epoxy Resin ER2188, Part A

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

**Product name** Epoxy Resin ER2188, Part A

**Product number** ER2188A, EER2188RP50G, EER2188RP50GF, EER2188RP100G, EER2188RP100GF,

EER2188RP250G, EER2188RP250GE, EER2188RP500G, EER2188RP1000G, EER2188RP1000GF, EER2188K5K, EER2188K10K, EER2188K25K, EER2188AB5K,

EER2188AB25K. ZE

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Resin.

**Uses advised against**No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier ELECTROLUBE. A division of HK WENTWORTH LTD

ASHBY PARK, COALFIELD WAY,

ASHBY DE LA ZOUCH, LEICESTERSHIRE LE65 1JR

UNITED KINGDOM +44 (0)1530 419600 +44 (0)1530 416640 info@hkw.co.uk

1.4. Emergency telephone number

Emergency telephone IN CASE OF EMERGENCY CALL:

+44 1865 407333 (24hr, Provided by Carechem 24)

+353 (0)1 809 2166 (Beaumont Hospital, Republic of Ireland only, 8am-10pm, 7 days a week)

## SECTION 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

**Environmental hazards** Aquatic Chronic 3 - H412

2.2. Label elements

Hazard pictograms



Signal word Warning

# Epoxy Resin ER2188, Part A

**Hazard statements** H315 Causes skin irritation.

H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** P261 Avoid breathing vapour/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular

weight ≤ 700), 2,3-epoxypropyl neodecanoate, formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

# 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

# 3.2. Mixtures

# Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin

10-30%

(number average molecular weight ≤ 700)

CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-

2119456619-26-XXXX

### Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Kaolin 1-5%

Classification

Not Classified

# Epoxy Resin ER2188, Part A

2,3-epoxypropyl neodecanoate

CAS number: 26761-45-5 EC number: 247-979-2 REACH registration number: 01-

2119431597-33-XXXX

Classification

Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

formaldehyde, oligomeric reaction products with 1-chloro-2,3-

0.1-1%

epoxypropane and phenol

CAS number: 9003-36-5 EC number: 500-006-8 REACH registration number: 01-

2119454392-40-0000

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

0.1-1%

CAS number: 68609-97-2 EC number: 271-846-8 REACH registration number: 01-

2119485289-22-XXXX

Classification

Skin Irrit. 2 - H315 Skin Sens. 1 - H317

The full text for all hazard statements is displayed in Section 16.

# SECTION 4: First aid measures

# 4.1. Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin contact It is important to remove the substance from the skin immediately. In the event of any

sensitisation symptoms developing, ensure further exposure is avoided. Remove

contamination with soap and water or recognised skin cleansing agent. Get medical attention

if symptoms are severe or persist after washing.

# Epoxy Resin ER2188, Part A

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue. If it is

> suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth

resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to

skin.

Eye contact Irritating to eyes.

## 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry Suitable extinguishing media

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapours.

### 5.3. Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

# Epoxy Resin ER2188, Part A

## Personal precautions

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid contact with skin and eyes.

# 6.2. Environmental precautions

### **Environmental precautions**

Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

# 6.3. Methods and material for containment and cleaning up

## Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

# 6.4. Reference to other sections

# Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

### Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

# Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

## Storage precautions

Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

# Storage class

Miscellaneous hazardous material storage.

# Epoxy Resin ER2188, Part A

# 7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

# SECTION 8: Exposure controls/Personal protection

## 8.1. Control parameters

# Occupational exposure limits

#### Kaolin

Long-term exposure limit (8-hour TWA): WEL 2 mg/m³ respirable dust WEL = Workplace Exposure Limit.

# 8.2. Exposure controls

### Protective equipment







# Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Wear tight-fitting, chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It is recommended that gloves are made of the following material: Nitrile rubber. Frequent changes are recommended.

# Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

# Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

# Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Organic vapour filter. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

# Epoxy Resin ER2188, Part A

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

**Appearance** Dark-coloured liquid.

Colour Black.

Odour Not known.

Odour threshold Not available.

**pH** Not available.

Melting point Not available.

**Initial boiling point and range** Not available.

Flash point Not available.

**Evaporation rate** Not available.

**Evaporation factor** Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Not available.

Other flammability Not available.

Vapour pressure Not available.

Vapour density Not available.

Relative density Not available.

Bulk density 1.83 kg/l

Solubility(ies) Not available.

Partition coefficient Not available.

Auto-ignition temperature Not available.

**Decomposition Temperature** Not available.

Viscosity 150000 mPa s @ 23°C

**Explosive properties** Not considered to be explosive.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

# SECTION 10: Stability and reactivity

# 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

# Epoxy Resin ER2188, Part A

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD<sub>∞</sub>) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause skin sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

**Genotoxicity - in vitro**Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

**IARC carcinogenicity**None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

# Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

# Specific target organ toxicity - repeated exposure

STOT - repeated exposure 
Not classified as a specific target organ toxicant after repeated exposure.

# Epoxy Resin ER2188, Part A

Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

**Ingestion** May cause sensitisation or allergic reactions in sensitive individuals. May cause irritation.

Skin contact May cause skin sensitisation or allergic reactions in sensitive individuals. Redness. Irritating to

skin.

**Eye contact** Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

**Target organs** No specific target organs known.

**Medical considerations** Skin disorders and allergies.

# SECTION 12: Ecological information

## 12.1. Toxicity

**Toxicity** Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

# 12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

## 12.5. Results of PBT and vPvB assessment

## 12.6. Other adverse effects

Other adverse effects None known.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

General information The generation of waste should be minimised or avoided wherever possible. Reuse or recycle

products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners

may retain some product residues and hence be potentially hazardous.

**Disposal methods**Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a

licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is

not feasible.

# Epoxy Resin ER2188, Part A

# **SECTION 14: Transport information**

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

### 14.1. UN number

Not applicable.

# 14.2. UN proper shipping name

Not applicable.

# 14.3. Transport hazard class(es)

No transport warning sign required.

### Transport labels

No transport warning sign required.

## 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

### Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Not applicable.

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment

Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].

EH40/2005 Workplace exposure limits.

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

# Inventories

## **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

## SECTION 16: Other information

# Epoxy Resin ER2188, Part A

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

RID: European Agreement concerning the International Carriage of Dangerous Goods by

Rail.

IATA: International Air Transport Association.

ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate.

LC₅o: Lethal Concentration to 50 % of a test population.

LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).

EC50: 50% of maximal Effective Concentration.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Classification abbreviations

and acronyms

Eye Irrit. = Eye irritation Skin Irrit. = Skin irritation

Skin Sens. = Skin sensitisation

Aquatic Chronic = Hazardous to the aquatic environment (chronic)

Classification procedures

according to Regulation (EC)

1272/2008

Skin Irrit. 2 - H315: Eye Irrit. 2 - H319: Skin Sens. 1 - H317: : Calculation method. Aquatic

Chronic 3 - H412: : Calculation method.

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

**Issued by** Damian Robertson

Revision date 21/04/2021

Revision 1.8

SDS number 699

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.