

Data Sheet

GS-213-3

Higher temperature version of GS-213

DESCRIPTION

GS-213-3 is a higher temperature version of GS-213. It has slightly lower tack and excellent clean-up on any surface. It is usable up to 232°C.

BENEFITS

- Lower tack level, so vacuum bags can be easily repositioned.
- High temperature rating for safer high temperature cures.
- Removes cleanly after cure reducing cost of tool cleaning.

TECHNICAL DATA

Colour	Light green
Base material	Synthetic rubber
Maximum use temperature	232°C
Shelf life	12 months from date of manufacture
Storage conditions	Tape must be stored flat in original packaging at 22°C Do not refrigerate

SIZES

Dimensions	Packaging
3 mm x 12 mm x 7,5 m (1/8 inch x 1/2 inch x 25 feet)	32 rolls per case
3 mm x 19 mm x 7,5 m (1/8 inch x 3/4 inch x 25 feet)	20 rolls per case



NOTES

- For clean removal, it is recommended to strip the tape from the mould surface once it has cooled down to room temperature.
- The maximum use temperature is dependent upon the duration at maximum temperature and is process specific, Airtech recommends testing prior to use.

Last updated : 2015-08-24

Catalogue position : [Vacuum bag sealant tapes](#)