



SAFETY DATA SHEET

DOW FRANCE S.A.S.

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: DOWSIL™ SE 4420 RTV Sealant

Revision Date: 21.11.2018

Version: 1.0

Date of last issue: -

Print Date: 22.11.2018

DOW FRANCE S.A.S. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name: DOWSIL™ SE 4420 RTV Sealant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Adhesive, binding agents

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

DOW FRANCE S.A.S.
23 AVENUE JULES RIMET
93210 LA PLAINE SAINT-DENIS
FRANCE

Customer Information Number:

(31) 115 67 2626
SDSQuestion@dow.com

1.4 EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 00 33 388 736 000

Local Emergency Contact: 00 33 388 736 000

ORFILA: + 33 (0)1 45 42 59 59

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008:

Flammable liquids - Category 3 - H226

Skin sensitisation - Category 1 - H317

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008:

Hazard pictograms**Signal word: WARNING****Hazard statements**

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P303 + P361 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 + P353
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Contains Methyltrimethoxysilane**2.3 Other hazards**

This product contains dodecamethylcyclohexasiloxane (D6) that has been identified by the Member State Committee of ECHA as fulfilling the vPvB criteria laid down in Annex XIII to Regulation (EC) No 1907/2006. See Section 12 for additional information.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone**3.2 Mixtures**

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN 1185-55-3 EC-No. 214-685-0 Index-No. -	01-2119517436-40	>= 1,9 - <= 2,0 %	Methyltrimethoxysilane	Flam. Liq. - 2 - H225 Skin Sens. - 1B - H317

PBT and vPvB substance

CASRN 540-97-6 EC-No. 208-762-8 Index-No. –	–	>= 0,45 - <= 0,47 %	Dodecamethyl cyclohexasiloxane	Not classified
---	---	---------------------	-----------------------------------	----------------

Substances with a workplace exposure limit

CASRN 1344-28-1 EC-No. 215-691-6 Index-No. –	01-2119529248-35	>= 71,0 - <= 74,0 %	Aluminum oxide	Not classified
--	------------------	---------------------	----------------	----------------

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical

Unsuitable extinguishing media: High volume water jet Do not use direct water stream.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides Formaldehyde Carbon oxides

Unusual Fire and Explosion Hazards: Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Vapours may form explosive mixtures with air.

5.3 Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up: Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling: Do not get on skin or clothing. Avoid inhalation of vapour or mist. Do not swallow. Avoid contact with eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent

spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ground and bond container and receiving equipment.

7.2 Conditions for safe storage, including any incompatibilities: Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

7.3 Specific end use(s): See the technical data sheet on this product for further information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Methyltrimethoxysilane	Dow IHG	TWA	7,5 ppm
	Dow IHG	TWA	Skin Sensitizer
Aluminum oxide	ACGIH	TWA Respirable fraction	1 mg/m ³ , Aluminium
	FR VLE	VME	10 mg/m ³
methanol	ACGIH	TWA	200 ppm
	ACGIH	STEL	250 ppm
	ACGIH	TWA	SKIN
	ACGIH	STEL	SKIN
	2006/15/EC	TWA	260 mg/m ³ 200 ppm
	2006/15/EC	TWA	SKIN
	FR VLE	VME	260 mg/m ³ 200 ppm
	FR VLE	VME	SKIN
FR VLE	VLCT (VLE)	1 300 mg/m ³ 1 000 ppm	
FR VLE	VLCT (VLE)	SKIN	

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:

Methanol.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
methanol	67-56-1	Methanol	Urine	End of shift (As)	15 mg/l	ACGIH BEI

soon as possible after exposure ceases)

Derived No Effect Level

Methyltrimethoxysilane

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
0,38 mg/kg bw/day	25,6 mg/m3	n.a.	n.a.	0,38 mg/kg bw/day	25,6 mg/m3	n.a.	n.a.

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
0,3 mg/kg bw/day	6,25 mg/m3	0,26 mg/kg bw/day	n.a.	n.a.	0,3 mg/kg bw/day	6,25 mg/m3	0,26 mg/kg bw/day	n.a.	n.a.

Dodecamethyl cyclohexasiloxane

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	6,1 mg/m3	n.a.	11 mg/m3	n.a.	1,22 mg/m3

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	1,7 mg/kg bw/day	n.a.	1,5 mg/m3	n.a.	2,7 mg/m3	1,7 mg/kg bw/day	n.a.	0,3 mg/m3

Aluminum oxide

Workers

<i>Acute systemic effects</i>		<i>Acute local effects</i>		<i>Long-term systemic effects</i>		<i>Long-term local effects</i>	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	15,63 mg/m3

Consumers

<i>Acute systemic effects</i>			<i>Acute local effects</i>		<i>Long-term systemic effects</i>			<i>Long-term local effects</i>	
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.

Predicted No Effect Concentration

Methyltrimethoxysilane

Compartment	PNEC
Fresh water	>= 1,3 mg/l
Marine water	>= 0,13 mg/l
Fresh water sediment	>= 1,1 mg/kg
Marine sediment	>= 0,11 mg/kg
Soil	>= 0,17 mg/kg
Sewage treatment plant	> 6,9 mg/l

Dodecamethyl cyclohexasiloxane

Compartment	PNEC
Fresh water sediment	2,826 mg/kg
Marine sediment	0,282 mg/kg
Soil	3,336 mg/kg
Sewage treatment plant	> 1,0 mg/l

Aluminum oxide

Compartment	PNEC
Fresh water	74,9 µg/l
Sewage treatment plant	20 mg/l

8.2 Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials

with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. When respiratory protection is required, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply.

Environmental exposure controls

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	viscous liquid
Color	white
Odor	slight
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 100 °C
Flash point	Seta closed cup 43 °C
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	2,25
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available

Dynamic Viscosity	80 000 mPa.s
Kinematic Viscosity	No data available
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weight	No data available
Particle size	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity: Not classified as a reactivity hazard.

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents. When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. Vapours may form explosive mixture with air. Flammable liquid and vapour.

10.4 Conditions to avoid: Heat, flames and sparks.

10.5 Incompatible materials: Oxidizing agents

10.6 Hazardous decomposition products: Methanol. Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): Estimated.

LD50, Rat, > 5 000 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Sensitization

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

The substance or mixture is not classified as specific target organ toxicant, single exposure.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Although certain forms of alumina have been reported to induce tumors when injected directly into the lungs of laboratory animals, there is no evidence that alumina is carcinogenic under normal routes of exposure.

Teratogenicity

High doses of aluminium and aluminium salts given to laboratory animals during pregnancy have caused developmental toxicity in the fetus at doses mildly toxic to the mother. The relevance of these data to alumina is unknown.

Reproductive toxicity

No relevant data found.

Mutagenicity

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Contains component(s) which were negative in some animal genetic toxicity studies and positive in others.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Methyltrimethoxysilane

Acute dermal toxicity

LD50, Rabbit, male and female, > 9 500 mg/kg

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, vapour, 51,6 mg/l

Dodecamethyl cyclohexasiloxane

Acute dermal toxicity

LD50, Rabbit, male and female, > 2 000 mg/kg

Acute inhalation toxicity

The LC50 has not been determined.

Aluminum oxide**Acute dermal toxicity**

The dermal LD50 has not been determined.

Acute inhalation toxicity

LC50, Rat, male and female, dust/mist, > 2,3 mg/l No deaths occurred at this concentration.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

12.1 Toxicity**Methyltrimethoxysilane****Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 110 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 122 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 120 mg/l, OECD Test Guideline 201

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, 120 mg/l, OECD Test Guideline 201

Dodecamethyl cyclohexasiloxane**Acute toxicity to algae/aquatic plants**

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 0,002 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, Daphnia magna (Water flea), 21 d, 0,0046 mg/l

Aluminum oxide**Acute toxicity to fish**

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

EC50, Fish, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Pimephales promelas (fathead minnow), 7 d, 7,1 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 28 d, 1,89 mg/l

12.2 Persistence and degradability

Methyltrimethoxysilane

Biodegradability: No relevant data found.

Dodecamethyl cyclohexasiloxane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 57 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

Aluminum oxide

Biodegradability: Biodegradability is not applicable to inorganic substances.

12.3 Bioaccumulative potential

Methyltrimethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -2,36

Dodecamethyl cyclohexasiloxane

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7).

Partition coefficient: n-octanol/water(log Pow): 8,87

Aluminum oxide

Bioaccumulation: Partitioning from water to n-octanol is not applicable.

12.4 Mobility in soil

Methyltrimethoxysilane

No relevant data found.

Dodecamethyl cyclohexasiloxane

Potential for mobility in soil is very high (Koc between 0 and 50).

Aluminum oxide

No relevant data found.

12.5 Results of PBT and vPvB assessment

Methyltrimethoxysilane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Dodecamethyl cyclohexasiloxane

Dodecamethyl cyclohexasiloxane (D6) meets the current REACh Annex XIII criteria for vPvB. However, D6 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D6 is not biomagnifying in aquatic and terrestrial food webs. D6 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D6 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

Aluminum oxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

12.6 Other adverse effects

Methyltrimethoxysilane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Dodecamethyl cyclohexasiloxane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Aluminum oxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

SECTION 14: TRANSPORT INFORMATION

Classification for ROAD and Rail transport (ADR/RID):

- 14.1 UN number UN 1993
- 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S.(Methyltrimethoxysilane)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered environmentally hazardous based on available data.
- 14.6 Special precautions for user Hazard Identification Number: 30

Classification for SEA transport (IMO-IMDG):

- 14.1 UN number UN 1993
- 14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S.(Methyltrimethoxysilane)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not considered as marine pollutant based on available data.
- 14.6 Special precautions for user EmS: F-E, S-E
- 14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

- 14.1 UN number UN 1993
- 14.2 UN proper shipping name Flammable liquid, n.o.s.(Methyltrimethoxysilane)
- 14.3 Transport hazard class(es) 3
- 14.4 Packing group III
- 14.5 Environmental hazards Not applicable
- 14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH). Polymers are exempted from registration under REACH. All relevant starting materials and additives have been either pre-registered, registered, or are exempt from registration to Regulation (EC) No. 1907/2006 (REACH). The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

Authorisation status under REACH:

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

CAS-No.: 540-97-6	Name: Dodecamethyl cyclohexasiloxane
-------------------	--------------------------------------

Authorisation status: listed in the Candidate List of Substances of Very High Concern for Authorisation

Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5 000 t

50 000 t

Installations classified for the protection of the environment (Environment Code R511-9)

4331: Flammable liquids category 2 or 3 excluding rubric 4330

Occupational Illnesses (R-461-3, France): (Not applicable)

Further information

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

Not applicable

SECTION 16: OTHER INFORMATION**Full text of H-Statements referred to under sections 2 and 3.**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Flam. Liq. - 3 - H226 - Based on product data or assessment

Skin Sens. - 1 - H317 - Calculation method

Revision

Identification Number: 6018622 / A560 / Issue Date: 21.11.2018 / Version: 1.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

2006/15/EC	Europe. Indicative occupational exposure limit values
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
Dow IHG	Dow Industrial Hygiene Guideline
FR VLE	France. Occupational Exposure Limits (INRS)
SKIN	Absorbed via skin
STEL	Short-term exposure limit
TWA	Time weighted average
VLCT (VLE)	Short Term Exposure Limit
VME	Time Weighted Average
Flam. Liq.	Flammable liquids
Skin Sens.	Skin sensitisation

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic

Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW FRANCE S.A.S. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

FR