

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : EPOCAST® 1610-A2 US

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe) BV
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1 800-424-9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	30.05.2023	400001018109	07.09.2018
			Date of first issue: 25.05.2016

Print Date 23.04.2024

Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Category 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P391 Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
1,4-bis(2,3 epoxypropoxy)butane
bisphenol A - epoxy resins, number average MW >700 - <1100
4-nonylphenol, branched

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 30 - < 50
1,4-bis(2,3 epoxypropoxy)butane	2425-79-8 219-371-7 603-072-00-7 01-2119494060-45	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 Acute toxicity estimate Acute dermal toxicity: 1 100 mg/kg	>= 3 - < 10
4-nonylphenol, branched	84852-15-3 284-325-5 601-053-00-8 01-2119510715-45	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361fd Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10 Acute toxicity estimate	>= 2,5 - < 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

		Acute oral toxicity: 1 412 mg/kg	
bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10
trimethoxy(methyl)silane	1185-55-3 214-685-0	Flam. Liq. 2; H225 STOT RE 2; H373 (Liver, Thyroid, Adrenal gland, Gastrointestinal tract)	>= 1 - < 10
hexaboron dizinc undecaoxide	12767-90-7 235-804-2	Eye Irrit. 2; H319 Repr. 2; H361d Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,25 - < 1
diuron (ISO)	330-54-1 206-354-4 006-015-00-9	Carc. 2; H351 Acute Tox. 4; H302 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1010 M-Factor (Chronic aquatic toxicity): 10	>= 0,25 - < 1
1,3,5-triazine-2,4,6-triamine	108-78-1 203-615-4 613-345-00-2	Repr. 2; H361	>= 0,1 - < 1

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	30.05.2023	400001018109	07.09.2018
			Date of first issue: 25.05.2016

Print Date 23.04.2024

personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue: 07.09.2018
1.2	30.05.2023	400001018109	Date of first issue: 25.05.2016

Print Date 23.04.2024

Hazardous combustion products : Carbon oxides
Halogenated compounds
Carbon dioxide (CO₂)
Carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Repeated or prolonged skin contact may cause skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

Avoid formation of respirable particles.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the application area.

Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 8 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
diuron (ISO)	330-54-1	VME	10 mg/m ³	FR VLE
Further information	Carcinogenic category 2 - Possibly carcinogenic to humans, Indicative exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 USVersion
1.2Revision Date:
30.05.2023SDS Number:
400001018109Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4,93 mg/m ³
	Workers	Dermal	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,87 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0,0893 mg/kg bw/day
1,4-bis(2,3 epoxypropoxy)butane	Consumers	Oral	Long-term systemic effects	0,5 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	4,7 mg/m ³
	Workers	Dermal	Long-term systemic effects	6,66 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,16 mg/m ³
cyanoguanidine	Consumers	Dermal	Long-term systemic effects	3,33 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,33 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	15,3 mg/m ³
	Workers	Inhalation	Acute systemic effects	76,5 mg/m ³
	Workers	Dermal	Long-term systemic effects	30,1 mg/kg
	Consumers	Inhalation	Long-term local effects	11,2 mg/m ³
	Consumers	Inhalation	Acute systemic effects	56 mg/m ³
	Consumers	Dermal	Long-term systemic effects	6,5 mg/kg
	Consumers	Oral	Long-term systemic effects	6,5 mg/kg
	Workers	Inhalation	Long-term systemic effects	8,3 mg/m ³
	Workers	Inhalation	Acute systemic effects	82,3 mg/m ³
	Workers	Dermal	Long-term systemic effects	11,8 mg/kg bw/day
	Workers	Dermal	Acute systemic effects	117 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,5 mg/m ³
	Consumers	Dermal	Long-term systemic effects	4,2 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,42 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version
1.2

Revision Date:
30.05.2023

SDS Number:
400001018109

Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l
	Marine water	0,001 mg/l
	Fresh water sediment	0,341 mg/kg dry weight (d.w.)
	Marine sediment	0,034 mg/kg dry weight (d.w.)
	Soil	0,065 mg/kg dry weight (d.w.)
	Sewage treatment plant	10 mg/l
	Secondary Poisoning	11 mg/kg
1,4-bis(2,3 epoxypropoxy)butane	Fresh water	0,024 mg/l
	Remarks:Assessment Factors	
	Marine water	0,002 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	100 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	0,084 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Marine sediment	0,008 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
cyanoguanidine	Soil	0,003 mg/kg dry weight (d.w.)
	Remarks:Equilibrium method	
	Oral	0,028 mg/kg
	Fresh water	2,5 mg/l
	Marine water	0,25 mg/l
	Freshwater - intermittent	10 mg/l
	Sewage treatment plant	34 mg/l
	Fresh water sediment	5,83 mg/kg
	Marine sediment	0,58 mg/kg
	Soil	3,16 mg/kg
1,3,5-triazine-2,4,6-triamine	Fresh water	0,51 mg/l
	Remarks:Assessment Factors	
	Freshwater - intermittent	2 mg/l
	Remarks:Assessment Factors	
	Marine water	0,051 mg/l
	Remarks:Assessment Factors	
	Sewage treatment plant	200 mg/l
	Remarks:Assessment Factors	
	Fresh water sediment	2,524
	Remarks:Equilibrium method	
Marine sediment	0,252	
Remarks:Equilibrium method		
Soil	0,206 mg/kg	
Remarks:Equilibrium method		

8.2 Exposure controls

Personal protective equipment

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Material : Nitrile rubber

Material : Neoprene
Break through time : 10 - 480 min

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : **W A R N I N G !** This product contains quartz, which has been classified by IARC as carcinogenic for humans (Group 1), and which can cause silicosis and lung cancer following exposure to respirable dust. It is therefore important to take particular care to avoid inhalation exposure when mechanically processing cured material (e.g. grinding, sanding, sawing).

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : solid, paste
Colour : off-white
Odour : slight
Odour Threshold : No data is available on the product itself.
pH : substance/mixture is non-soluble (in water)
Melting point/freezing point : No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Boiling point : > 200 °C

Flash point : > 94 °C
Method: closed cup

Flammability (solid, gas) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : < 1,333 hPa (20 °C)

Relative vapour density : 1

Relative density : 0,46 - 0,5

Density : 0,48 g/cm³ (25 °C)

Solubility(ies)
Water solubility : insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Dust may form explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2 000 mg/kg
Method: Calculation method

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

1,4-bis(2,3 epoxypropoxy)butane:

Acute oral toxicity : LD50 (Rat, male and female): 1 163 mg/kg
Method: OECD Test Guideline 401
GLP: yes
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 2,068 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Test atmosphere: dust/mist
Method: Expert judgement
Assessment: The component/mixture is moderately toxic after short term inhalation., The substance/mixture is not toxic on inhalation as defined by dangerous goods regulations.

Acute dermal toxicity : Acute toxicity estimate: 1 100 mg/kg
Method: Converted acute toxicity point estimate

Assessment: The component/mixture is moderately toxic after single contact with skin.

4-nonylphenol, branched:

Acute oral toxicity : LD50 (Rat, male and female): 1 412 mg/kg

Acute toxicity estimate: 1 412 mg/kg
Method: Calculation method

Acute dermal toxicity : LD50 (Rabbit, male): 2 031 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

trimethoxy(methyl)silane:

Acute oral toxicity : LD50 (Rat, male): 11 685 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 7605 ppm
Exposure time: 6 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 9 500 mg/kg
Method: OECD Test Guideline 402

diuron (ISO):

Acute oral toxicity : LD50 (Rat, female): 4 150 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,05 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

LC50 (Rat): > 7,1 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OPPTS 870.1300

Acute dermal toxicity : LD50 (Rat, male and female): > 5 000 mg/kg
Method: OECD Test Guideline 402

LD50 (Rat, male and female): > 2 000 mg/kg
Method: OPPTS 870.1200

1,3,5-triazine-2,4,6-triamine:

Acute oral toxicity : LD50 (Rat, male and female): 3 161 - 3 828 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5190 mg/m3
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit
Exposure time : 4 h
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation
GLP : yes

4-nonylphenol, branched:

Species : Rabbit
Assessment : Causes burns.
Result : Causes burns.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Method : OECD Test Guideline 404
Result : Skin irritation

trimethoxy(methyl)silane:

Species : Rabbit
Assessment : No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Method : OECD Test Guideline 404
Result : No skin irritation

diuron (ISO):

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

Species : Rabbit
Assessment : Mild skin irritant
Method : OPPTS 870.2500
Result : Mild skin irritation

1,3,5-triazine-2,4,6-triamine:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 405
Result : Irritating to eyes.

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rabbit
Assessment : Risk of serious damage to eyes.
Method : OECD Test Guideline 405
GLP : yes

4-nonylphenol, branched:

Result : Risk of serious damage to eyes.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Eye irritation

trimethoxy(methyl)silane:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

hexaboron dizinc undecaoxide:

Assessment : Irritating to eyes.

diuron (ISO):

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 7 days

Species : Rabbit
Assessment : Mild eye irritant
Method : OPPTS 870.2400
Result : Irritation to eyes, reversing within 7 days

1,3,5-triazine-2,4,6-triamine:

Species : Rabbit
Remarks : slight irritation

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin
Species : Mouse
Method : OECD Test Guideline 429
Result : The product is a skin sensitiser, sub-category 1B.

1,4-bis(2,3 epoxypropoxy)butane:

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitisation by skin contact.
GLP : yes

Assessment : Harmful if inhaled.

4-nonylphenol, branched:

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : May cause sensitisation by skin contact.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

trimethoxy(methyl)silane:

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Causes sensitisation.

diuron (ISO):

Exposure routes : Skin
Species : Guinea pig
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Exposure routes : Skin
Species : Guinea pig
Method : OPPTS 870.2600
Result : Does not cause skin sensitisation.

1,3,5-triazine-2,4,6-triamine:

Test Type : Maximisation Test
Exposure routes : Skin
Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.
GLP : yes

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: without metabolic activation
Result: positive

Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay
Species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Species: Rat (male)
Cell type: Somatic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

1,4-bis(2,3 epoxypropoxy)butane:

Genotoxicity in vitro : Test Type: reverse mutation assay
Concentration: 10 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster lung cells
Concentration: 1 - 100 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive
GLP: yes
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster lung cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive
GLP: no
Remarks: Not classified due to data which are conclusive although insufficient for classification.

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse (male)
Cell type: Somatic
Application Route: Oral
Exposure time: 4 d
Dose: 187.5 - 750 mg/kg
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Germ cell mutagenicity-Assessment : Weight of evidence does not support classification as a germ cell mutagen., Animal testing did not show any mutagenic effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: Positive results were obtained in some in vitro tests.

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

trimethoxy(methyl)silane:

Genotoxicity in vivo : Application Route: Oral
Dose: 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative

diuron (ISO):

Genotoxicity in vitro : Concentration: 360 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Concentration: 2000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection
Dose: 700 mg/kg
Method: OECD Test Guideline 474
Result: negative

1,3,5-triazine-2,4,6-triamine:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Test Type: gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Mouse (male)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 0 - 150 - 300 - 600 mg/kg
Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOAEL : 15 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Mouse, male
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0, 0.1, 10, 100 mg/kg bw/day
Frequency of Treatment : 3 days/week
NOEL : 0,1 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Rat, female
Application Route : Dermal
Exposure time : 24 month(s)
Dose : 0.1, 100, 1000 mg/kg bw/day
Frequency of Treatment : 5 days/week
NOEL : 100 mg/kg body weight
Method : OECD Test Guideline 453
Result : negative

Species : Rat, female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Frequency of Treatment : 7 days/week
NOAEL : 100 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

Species : Rat, females
Application Route : Oral
Exposure time : 24 month(s)
Dose : 0, 2, 15, or 100 mg/kg bw/day
Frequency of Treatment : 7 days/week
NOEL : 2 mg/kg bw/day
Method : OECD Test Guideline 453
Result : negative
Target Organs : Digestive organs

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 15 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : negative

diuron (ISO):

Species : Rat, male and female
Application Route : Oral
Exposure time : 24 month(s)
Dose : 1 - 17 mg/kg
Frequency of Treatment : 7 daily
Method : OECD Test Guideline 453
Result : positive
Target Organs : Bladder

Species : Rat, male and female
Application Route : Oral
Dose : < 600 mg/kg
Result : positive

1,3,5-triazine-2,4,6-triamine:

Species : Rat, male and female
Application Route : Oral
Exposure time : 103 weeks
NOAEL : 126 mg/kg bw/day
Result : negative
Target Organs : Urinary bladder

Species : Mouse, male and female
Application Route : Oral
Exposure time : 103 weeks
NOAEL : 2 250 mg/kg bw/day
Result : negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 180, 540 or 750 milligram per kilogram
Duration of Single Treatment: 238 d
Frequency of Treatment: 1 daily
General Toxicity - Parent: NOEL: 540 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Developmental Toxicity: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Developmental Toxicity: NOAEL: > 540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

1,4-bis(2,3 epoxypropoxy)butane:

Effects on foetal development : Test Type: Pre-natal
Species: Rat, female
Application Route: Oral

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Dose: 0/30/100/300 mg/kg bw/day
Duration of Single Treatment: 17 d
General Toxicity Maternal: NOAEL: 300 mg/kg body weight
Developmental Toxicity: NOAEL: 300 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes
Remarks: Information given is based on data obtained from similar substances.

4-nonylphenol, branched:

Effects on foetal development : Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 75 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : Suspected human reproductive toxicant

bisphenol A - epoxy resins, number average MW >700 - <1100:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
General Toxicity - Parent: NOEL: 750 mg/kg body weight
General Toxicity F1: NOEL: 750 mg/kg body weight
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

trimethoxy(methyl)silane:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422
Result: negative

Effects on foetal : Species: Rat, male and female

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

development

Application Route: Oral
General Toxicity Maternal: NOAEL: 1 000 mg/kg body weight
Method: OECD Test Guideline 422
Result: No teratogenic effects

hexaboron dizinc undecaoxide:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

diuron (ISO):

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development

: Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 16 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 10 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: > 125 mg/kg body weight
Result: Teratogenic effects

1,3,5-triazine-2,4,6-triamine:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Dose: 1000/4000/12500 pm
General Toxicity - Parent: NOAEL: 1 000 ppm
General Toxicity F1: NOAEL: >= 12 500 ppm
General Toxicity F2: NOAEL: >= 12 500 parts per million
Target Organs: Testes
Method: OECD Test Guideline 443
GLP: yes

Effects on foetal development

: Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOAEL: 600 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 136; 400; 1060 mg/kg bw/day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Duration of Single Treatment: 11 d
General Toxicity Maternal: NOAEL: ca. 400 mg/kg body weight
Developmental Toxicity: NOAEL: ca. 1 060 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 15/50/150 mg/kg bw/d
Duration of Single Treatment: 23 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: NOAEL: 150 mg/kg body weight
Developmental Toxicity: NOAEL: 150 mg/kg body weight
Method: OECD Test Guideline 414
GLP: yes

Reproductive toxicity - Assessment : Suspected of damaging fertility or the unborn child., Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT - single exposure

No data available

STOT - repeated exposure

Components:

trimethoxy(methyl)silane:

Target Organs : Liver, Thyroid, Adrenal gland, Gastrointestinal tract
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : oral (gavage)
Exposure time : 14 Weeks
Number of exposures : 7 d
Dose : 0, 50, 250, 1000 mg/kg/day
Method : OECD Test Guideline 408

Species : Rat, male and female
NOAEL : >= 10 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 5 d
Dose : 0, 10, 100, 1000 mg/kg/day
Method : OECD Test Guideline 411

Species : Mouse, male

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

NOAEL : 100 mg/kg
Application Route : Skin contact
Exposure time : 13 Weeks
Number of exposures : 3 d
Dose : 0, 1, 10, 100 mg/kg/day
Method : OECD Test Guideline 411

1,4-bis(2,3 epoxypropoxy)butane:

Species : Rat, male and female
NOAEL : 200 mg/kg
Application Route : Oral
Exposure time : 28 d
Number of exposures : daily
Dose : 25, 100, 200, 400 mg/kg
Method : Subacute toxicity

Species : Rat, male and female
NOAEL : 263 mg/kg
Application Route : Oral
Exposure time : 90 h
Number of exposures : daily
Dose : 0,30,100,300 mg/kg bw/day
Method : OECD Test Guideline 408
GLP : yes
Remarks : Information given is based on data obtained from similar substances.

4-nonylphenol, branched:

Species : Rat, male and female
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 672 h
Number of exposures : 7 d
Method : Subacute toxicity

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 2 160 h
Number of exposures : 7 d
Method : Subchronic toxicity

bisphenol A - epoxy resins, number average MW >700 - <1100:

Species : Rat, male and female
NOAEL : 50 mg/kg
Application Route : Ingestion
Exposure time : 14 Weeks
Number of exposures : 7 d
Method : Subchronic toxicity

Species : Rat, male and female
NOEL : 10 mg/kg
Application Route : Skin contact

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Exposure time : 13 Weeks
Number of exposures : 5 d
Method : Subchronic toxicity

trimethoxy(methyl)silane:

Species : Rat, male and female
NOEC : 50 mg/kg, 100 ppm
Application Route : Ingestion
Test atmosphere : vapour
Exposure time : 672 h
Number of exposures : 7 d
Method : OECD Test Guideline 413

diuron (ISO):

Species : Rat, male and female
NOEC : 6,7 - 8,7 mg/kg, 4,1 - 37,4 mg/m³
Application Route : Inhalation
Test atmosphere : dust/mist
Exposure time : 8 Weeks
Number of exposures : 7 d
Method : OECD Test Guideline 412

Species : Dog, male and female
NOAEL : 1,8 mg/kg/d
Application Route : Ingestion
Exposure time : 8 640 h
Number of exposures : 7 d
Method : Chronic toxicity

Species : Rabbit, male and female
NOAEL : 250 mg/kg/d
Application Route : Skin contact
Exposure time : 504 h
Number of exposures : 5 d
Method : Subacute toxicity

1,3,5-triazine-2,4,6-triamine:

Species : Rat, male
NOAEL : 72 mg/kg
Application Route : oral (feed)
Exposure time : 13 Weeks
Method : Subchronic toxicity

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Experience with human exposure

No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,8 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 : 11 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4,2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

1,4-bis(2,3 epoxypropoxy)butane:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l
End point: mortality
Exposure time: 96 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 203
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l
End point: Immobilization
Exposure time: 24 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 202
GLP: no

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 160 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

NOELR (Pseudokirchneriella subcapitata (green algae)): 40 mg/l
Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209
GLP: no

4-nonylphenol, branched:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0,128 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	30.05.2023	400001018109	07.09.2018
			Date of first issue: 25.05.2016

Print Date 23.04.2024

Test Type: flow-through test
Test substance: Fresh water
Method: ASTM Method, other

LC50 (Lepomis macrochirus (Bluegill sunfish)): 0,209 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water
Method: ASTM Method, other

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,221 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water
Method: ASTM Method, other

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,085 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: ASTM Method, other

EC50 (Daphnia magna (Water flea)): 0,14 mg/l
Exposure time: 48 h
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : EbC50 (Desmodesmus subspicatus (green algae)): 1,3 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

ErC50 (Selenastrum capricornutum (green algae)): 0,41 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: Algal Toxicity, Tiers I and II

M-Factor (Acute aquatic toxicity) : 10

Toxicity to microorganisms : EC50 (activated sludge): 950 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,006 mg/l
Exposure time: 91 d
Species: Oncorhynchus mykiss (rainbow trout)
Test Type: flow-through test
Test substance: Fresh water

M-Factor (Chronic aquatic toxicity) : 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Toxicity to soil dwelling organisms : EC10: 3,44 mg/kg
Exposure time: 504 h

EC50: 906,7 mg/kg
Exposure time: 4 Weeks
Species: Other
Test substance: Synthetic

Toxicity to terrestrial organisms : EC10: 63,2 mg/kg
Exposure time: 672 h
Test substance: Synthetic

bisphenol A - epoxy resins, number average MW >700 - <1100:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

trimethoxy(methyl)silane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l
Exposure time: 96 h
Test Type: flow-through test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 122 mg/l
Exposure time: 48 h
Test Type: flow-through test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 120 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

hexaboron dizinc undecaoxide:

Toxicity to fish : LC50 : 0,169 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

End point: mortality
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 0,025 mg/l

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

diuron (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 14,7 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

LC50 (Pimephales promelas (fathead minnow)): 14 mg/l
Exposure time: 96 h
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,4 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Other): 22 ug/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

EC50 (Selenastrum capricornutum (green algae)): 2.4 ppb
Exposure time: 96 h
Test substance: Fresh water

M-Factor (Acute aquatic toxicity) : 10

10

Toxicity to microorganisms : EC50 (activated sludge): 3 080 mg/l
Exposure time: 0,5 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

Toxicity to fish (Chronic) : NOEC: 0,41 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

toxicity) Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,56 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

NOEC: >= 1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water

M-Factor (Chronic aquatic toxicity) : 10

Toxicity to soil dwelling organisms : LC50: > 1 000 mg/kg
Exposure time: 336 h
Species: Eisenia fetida (earthworms)

Species: Eisenia fetida (earthworms)
Remarks: see user defined free text

1,3,5-triazine-2,4,6-triamine:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 3 000 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
GLP: no

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 200 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
GLP: yes

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 325 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 98 mg/l
Exposure time: 96 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Test substance: Fresh water
GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC: \geq 5 mg/l
Exposure time: 36 d
Species: Pimephales promelas (fathead minnow)
Test Type: flow-through test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 210
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 11 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 211
GLP: yes

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

1,4-bis(2,3 epoxypropoxy)butane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 43 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue: 07.09.2018
1.2	30.05.2023	400001018109	Date of first issue: 25.05.2016

Print Date 23.04.2024

Exposure time: 28 d
Method: OECD Test Guideline 301F
GLP: yes

Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 38 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 301E
GLP: no

4-nonylphenol, branched:

Biodegradability : Inoculum: activated sludge
Concentration: 13 mg/l
Result: Inherently biodegradable.
Biodegradation: ca. 48,2 %
Exposure time: 35 d
Method: OECD Test Guideline 301B

Inoculum: Sediment
Concentration: 2
Result: Inherently biodegradable.
Biodegradation: 100 %
Exposure time: 63 - 84 d
Method: Anaerobic Biodegradability in the Subsurface

Inoculum: Marine water
Concentration: 11
Biodegradation: 50 %
Exposure time: 56 - 112 d
Method: OECD Test Guideline 309

bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not biodegradable
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

trimethoxy(methyl)silane:

Biodegradability : Inoculum: activated sludge
Concentration: 11,2 mg/l
Result: Not readily biodegradable.
Biodegradation: 54 %
Exposure time: 28 d

Stability in water : Degradation half life (DT50): 2,2 hrs (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

hexaboron dizinc undecaoxide:

Biodegradability : Result: Readily biodegradable.

diuron (ISO):

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 30 mg/l
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Result: Inherently biodegradable.

1,3,5-triazine-2,4,6-triamine:

Biodegradability : Inoculum: activated sludge
Concentration: 100 mg/l
Result: Not readily biodegradable.
Biodegradation: < 10 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 28 d
Method: OECD Test Guideline 302B
Test substance: Fresh water

Inoculum: activated sludge
Concentration: 100 parts per million
Result: Not biodegradable
Method: OECD Test Guideline 301C
Test substance: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue: 07.09.2018
1.2	30.05.2023	400001018109	Date of first issue: 25.05.2016

Print Date 23.04.2024

Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

1,4-bis(2,3 epoxypropoxy)butane:

Partition coefficient: n-octanol/water : log Pow: -0,269 (25 °C)
pH: 6,7
Method: OECD Test Guideline 117
GLP: yes

4-nonylphenol, branched:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 231
Remarks: Does not bioaccumulate.

Species: Pimephales promelas (fathead minnow)
Bioconcentration factor (BCF): 740
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 5,4 (23 °C)
pH: 5,7
Method: OECD Test Guideline 117

bisphenol A - epoxy resins, number average MW >700 - <1100:

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

trimethoxy(methyl)silane:

Partition coefficient: n-octanol/water : log Pow: 0,7 (20 °C)
pH: 7
Method: QSAR

diuron (ISO):

Bioaccumulation : Species: Other
Bioconcentration factor (BCF): 5,2
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2,89 (20 °C)
pH: 7,01
Method: OECD Test Guideline 107

1,3,5-triazine-2,4,6-triamine:

Partition coefficient: n-octanol/water : log Pow: -1,22 (20 °C)
pH: 8
Method: Partition coefficient
GLP: no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

1,4-bis(2,3 epoxypropoxy)butane:

Distribution among environmental compartments : Koc: 12,59
Method: OECD Test Guideline 121

4-nonylphenol, branched:

Distribution among environmental compartments : Koc: 23000 - 489000

bisphenol A - epoxy resins, number average MW >700 - <1100:

Distribution among environmental compartments : Koc: 445

diuron (ISO):

Distribution among environmental compartments : Koc: 293 - 504
Method: OECD Test Guideline 106

1,3,5-triazine-2,4,6-triamine:

Distribution among environmental compartments : Koc: 1,7

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : This substance/mixture contains components considered to have endocrine disrupting properties for environment, according to REACH Article 57(f), Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

Components:

4-nonylphenol, branched:

Assessment : The substance is considered to have endocrine disrupting properties according to REACH Article 57(f) for the environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of contents and container in accordance with all local, regional, national and international regulations.
Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 3077
ADR : UN 3077
RID : UN 3077
IMDG : UN 3077
IATA : UN 3077

14.2 UN proper shipping name

ADN : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(NONYL PHENOL, DIURON)
ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(NONYL PHENOL, DIURON)
RID : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(NONYL PHENOL, DIURON)
IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(NONYL PHENOL, DIURON)
IATA : Environmentally hazardous substance, solid, n.o.s.
(NONYL PHENOL, DIURON)

14.3 Transport hazard class(es)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

	Class	Subsidiary risks
ADN	: 9	
ADR	: 9	
RID	: 9	
IMDG	: 9	
IATA	: 9	

14.4 Packing group

ADN

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

ADR

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9
Tunnel restriction code : (-)

RID

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	30.05.2023	400001018109	07.09.2018
			Date of first issue: 25.05.2016

Print Date 23.04.2024

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : 4-nonylphenol, branched

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

4-nonylphenol, branched (Number on list 46a)
formaldehyde (Number on list 72, 28)
benzene (Number on list 72, 5, 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E1 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the : 4510

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue: 07.09.2018
1.2	30.05.2023	400001018109	Date of first issue: 25.05.2016

Print Date 23.04.2024

protection of the environment
(Environment Code R511-9)

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AIIC	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: Not in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version 1.2 Revision Date: 30.05.2023 SDS Number: 400001018109 Date of last issue: 07.09.2018
Date of first issue: 25.05.2016

Print Date 23.04.2024

H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H351 : Suspected of causing cancer.
H361 : Suspected of damaging fertility or the unborn child.
H361d : Suspected of damaging the unborn child.
H361fd : Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
FR VLE : France. Occupational Exposure Limits
FR VLE / VME : Time Weighted Average

Further information

Classification of the mixture:

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1610-A2 US

Version	Revision Date:	SDS Number:	Date of last issue: 07.09.2018
1.2	30.05.2023	400001018109	Date of first issue: 25.05.2016

Print Date 23.04.2024

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.