

# SAFETY DATA SHEET



## DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White

Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

### SECTION 1. IDENTIFICATION

Product name : DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White

Product code : 04001705

#### Manufacturer or supplier's details

Company Identification : THE DOW CHEMICAL COMPANY  
2030 DOW CENTER  
MIDLAND MI 48674-0000  
UNITED STATES

Telephone : 800-258-2436

24-Hour Emergency Contact : Chemtrec +1 800-424-9300

Local Emergency Number : 800-424-9300

E-mail address : SDSQuestion@dow.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

### SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

Precautionary Statements : **Prevention:**  
P271 Use only outdoors or in a well-ventilated area.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone

#### Hazardous ingredients

Chemical name	CAS-No	Concentration (% w/w)
Calcium carbonate	471-34-1	>= 30 - < 50
Amorphous fumed silica	112945-52-5	>= 1 - < 5
Titanium(4+) 2-methylpropan-2-olate	3087-39-6	>= 1 - < 5

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

Quartz      14808-60-7      >= 0.1 - < 1

#### SECTION 4. FIRST AID MEASURES

General advice	: In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: None known.
Protection of first-aiders	: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
Notes to physician	: Treat symptomatically and supportively.

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Water spray Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Silicon oxides Formaldehyde Metal oxides

## SAFETY DATA SHEET



### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White

Version	Revision Date:	SDS Number:	Date of last issue:
5.0	10/18/2017	904155-00008	04/27/2017
			Date of first issue: 12/05/2014

---

- II**
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

#### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.
-

## SAFETY DATA SHEET

## DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00006      Date of last issue: 04/27/2017  
 Date of first issue: 12/05/2014

- Conditions for safe storage : Keep in properly labeled containers.  
 Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
 Strong oxidizing agents

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Amorphous fumed silica	112945-52-5	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Quartz	14808-60-7	TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1

## Hazardous components without workplace control parameters

Ingredients	CAS-No.
Titanium(4+) 2-methylpropan-2-olate	3087-39-6

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Calcium carbonate

Amorphous fumed silica

Quartz

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

---

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

**Respiratory protection** : No personal respiratory protective equipment normally required.

#### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection** : Skin should be washed after contact.

**Hygiene measures** : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

---

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : paste

**Color** : white to off-white

**Odor** : alcohol-like

**Odor Threshold** : No data available

**pH** : Not applicable

**Melting point/freezing point** : No data available

**Initial boiling point and boiling range** : Not applicable

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

---

Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Not classified as a flammability hazard
Self-ignition	:	The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	No data available
Relative density	:	1.35
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available

---

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Methyl alcohol is formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.

# SAFETY DATA SHEET



## DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White

Version	Revision Date:	SDS Number:	Date of last issue:
5.0	10/18/2017	904155-00008	04/27/2017
			Date of first issue: 12/05/2014

Conditions to avoid : None known.  
Incompatible materials : Oxidizing agents

**Hazardous decomposition products**  
Thermal decomposition : Formaldehyde

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Ingredients:

##### Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

##### Amorphous fumed silica:

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Assessment: The substance or mixture has no acute dermal

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version  
5.0

Revision Date:  
10/18/2017

SDS Number:  
904155-00008

Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

toxicity  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

#### Titanium(4+) 2-methylpropan-2-olate:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

#### Quartz:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

#### Skin corrosion/irritation

Not classified based on available information.

#### Ingredients:

##### Calcium carbonate:

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

##### Amorphous fumed silica:

Species: Rabbit  
Result: No skin irritation  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

#### Titanium(4+) 2-methylpropan-2-olate:

Result: Skin irritation

#### Serious eye damage/eye irritation

Not classified based on available information.

#### Ingredients:

##### Calcium carbonate:

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405

##### Amorphous fumed silica:

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials  
Information taken from reference works and the literature.

#### Titanium(4+) 2-methylpropan-2-olate:

Result: Irritation to eyes, reversing within 21 days



# SAFETY DATA SHEET



## DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White

Version 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

---

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Ingredients:

##### Calcium carbonate:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse

Method: OECD Test Guideline 429

Result: negative

#### Germ cell mutagenicity

Not classified based on available information.

#### Ingredients:

##### Calcium carbonate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative

#### Carcinogenicity

Not classified based on available information.

#### Ingredients:

##### Quartz:

Species: Humans

Application Route: inhalation (dust/mist/fume)

Result: positive

Remarks: IARC: (International Agency for Research on Cancer)

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

IARC      Group 1: Carcinogenic to humans

Quartz      14808-60-7

OSHA      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP      Known to be human carcinogen

Quartz      14808-60-7

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version: 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
Date of first issue: 12/05/2014

#### Reproductive toxicity

Not classified based on available information.

#### Ingredients:

##### Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### Ingredients:

##### Quartz:

Routes of exposure: inhalation (dust/mist/fume)  
Target Organs: Lungs  
Assessment: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

#### Repeated dose toxicity

#### Ingredients:

##### Calcium carbonate:

Species: Rat  
NOAEL: 1,000 mg/kg  
Application Route: Ingestion  
Exposure time: 6 Weeks  
Method: OECD Test Guideline 422

##### Quartz:

Species: Humans  
LOAEL: 0.053 mg/m<sup>3</sup>  
Application Route: Inhalation  
Remarks: These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2017
5.0	10/18/2017	904155-00008	Date of first issue: 12/05/2014

#### Aspiration toxicity

Not classified based on available information.

## SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Ingredients:

##### Calcium carbonate:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae	:	ErC50 (Desmodesmus subspicatus (green algae)): > 14 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

##### Quartz:

##### Ecotoxicology Assessment

Acute aquatic toxicity	:	No toxicity at the limit of solubility.
Chronic aquatic toxicity	:	No toxicity at the limit of solubility.

##### Persistence and degradability

No data available

##### Bioaccumulative potential

No data available

##### Mobility in soil

No data available

##### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

##### Disposal methods

Resource Conservation and Recovery Act (RCRA)	:	This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.
Waste from residues	:	Dispose of in accordance with local regulations.
Contaminated packaging	:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

## SAFETY DATA SHEET


**DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White**

Version 5.0	Revision Date: 10/18/2017	SDS Number: 904155-00008	Date of last issue: 04/27/2017 Date of first issue: 12/05/2014
----------------	------------------------------	-----------------------------	---

If not otherwise specified: Dispose of as unused product.

## SECTION 14. TRANSPORT INFORMATION

## International Regulations

## UNRTDG

Not regulated as a dangerous good

## IATA-DGR

Not regulated as a dangerous good

## IMDG-Code

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## Domestic regulation

## 49 CFR

Not regulated as a dangerous good

## SECTION 15. REGULATORY INFORMATION

## EPCRA - Emergency Planning and Community Right-to-Know

## CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

## SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

## US State Regulations

## Pennsylvania Right To Know

Dimethyl siloxane, trimethoxysilyl-terminated	Not Assigned
Calcium carbonate	471-34-1
Dimethyl siloxane, trimethylsiloxy-terminated	63148-62-9
Amorphous fumed silica	112945-52-5
Methanol	67-56-1
tert-Butyl alcohol	75-65-0

# SAFETY DATA SHEET

## DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version: 5.0      Revision Date: 10/18/2017      SDS Number: 904155-00008      Date of last issue: 04/27/2017  
 Date of first issue: 12/05/2014

### California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Permissible Exposure Limits for Chemical Contaminants

Calcium carbonate	471-34-1
Amorphous fumed silica	112945-52-5

### California Regulated Carcinogens

Quartz	14808-60-7
--------	------------


### The ingredients of this product are reported in the following inventories:

- TSCA** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
- IECSC** : All ingredients listed or exempt.
- DSL** : This product contains one or more substances which are not on the Canadian Domestic Substances List (DSL). Import of this product into Canada has volume limitations. For volume limits please consult Dow Chemical Regulatory Compliance.

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "1" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 NIOSH REL : USA. NIOSH Recommended Exposure Limits  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
 OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2017
5.0	10/18/2017	904155-00008	Date of first issue: 12/05/2014

ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

eral Dusts

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoc - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/18/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided

## SAFETY DATA SHEET

### DOWSIL™ 9-1363 Industrial Assembly Adhesive Sealant White



Version	Revision Date:	SDS Number:	Date of last issue: 04/27/2017
5.0	10/18/2017	904155-00008	Date of first issue: 12/05/2014

---

relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8