

## SAFETY DATA SHEET

#### DOW FRANCE S.A.S.

Safety Data Sheet according to Reg. (EU) No 2015/830

**Product name: SYLGARD™ 3-6605 Thermally Conductive** 

**Elastomer Part B** 

Revision Date: 18.10.2019 Version: 1.0 Date of last issue: -

Print Date: 19.10.2019

DOW FRANCE S.A.S. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product name: SYLGARD™ 3-6605 Thermally Conductive Elastomer Part B

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Adhesive, binding agents

## 1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

DOW FRANCE S.A.S. 23 AVENUE JULES RIMET 93210 LA PLAINE SAINT-DENIS FRANCE

Customer Information Number: (31) 115 67 2626

SDSQuestion@dow.com

#### 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 00 33 388 736 000 **Local Emergency Contact:** 00 33 388 736 000

ORFILA: + 33 (0)1 45 42 59 59

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008:

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

## **Precautionary statements**

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smokina.

P234 Keep only in original packaging. P403 Store in a well-ventilated place.

#### 2.3 Other hazards

May generate flammable hydrogen gas. Avoid contact with water, alcohols, acidic, basic, or oxidizing materials.

This product contains dodecamethylcyclohexasiloxane (D6) that has been identified by the Member State Committee of ECHA as fulfilling the vPvB criteria laid down in Annex XIII to Regulation (EC) No 1907/2006. See Section 12 for additional information.

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature: Silicone

3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
PBT and vPvB s	substance			
CASRN 540-97-6 EC-No. 208-762-8 Index-No.	_	>= 0,27 - <= 0,28 %	Dodecamethyl cyclohexasiloxane	Not classified
Substances with	n a workplace exposu	re limit		
CASRN Not available EC-No. Not available Index-No.	-	>= 67,0 - <= 71,0 %	Methyltrimethoxysil ane treated aluminum oxide	Not classified
CASRN Not available EC-No. Not available Index-No.	_	>= 1,4 - <= 1,5 %	Methyl trimethoxysilane- treated silica	Not classified

## **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures

Page 2 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

#### General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

**Skin contact:** Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Ingestion:** Rinse mouth thoroughly with water. No emergency medical treatment necessary.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

4.3 Indication of any immediate medical attention and special treatment needed Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1 Extinguishing media

Suitable extinguishing media: Water spray. Alcohol-resistant foam. Carbon dioxide (CO2).

Unsuitable extinguishing media: Dry chemical.

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: Silicon oxides. Metal oxides. Formaldehyde. Carbon oxides.

Unusual Fire and Explosion Hazards: Applying foam will release significant amounts of hydrogen gas that can be trapped under the foam blanket.. Exposure to combustion products may be a hazard to health...

## 5.3 Advice for firefighters

Fire Fighting Procedures: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Do not allow extinguishing medium to contact container contents. Most fire extinguishing media will cause hydrogen evolution, and once the fire is put out, may accumulate in poorly ventilated or confined areas and result in flash fire or explosion if ignited. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Page 3 of 18

Product name: SYLGARD™ 3-6605 Thermally Conductive Revision Date: 18.10.2019

Elastomer Part B Version: 1.0

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

- **6.1 Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations.
- **6.2 Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- **6.3 Methods and materials for containment and cleaning up:** Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Materials in contact with water, moisture, acids or bases have the potential to generate hydrogen gas. Recovered material should bestored in a vented container. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. Recovered material should be stored in a vented container. The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to overpressurization of the container.

#### 6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

## **SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:** Keep away from water. Protect from moisture. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in properly labelled containers. Store in original container. Store in accordance with the particular national regulations. Product may evolve minute quantities of flammable hydrogen gas which can accumulate. Adequately ventilate to maintain vapors well below flammability limits and exposure guidelines. Do not repackage. Clogged container vents may increase pressure build up. Store in a closed container.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: Do not store in or use containers except the original product package.

**7.3 Specific end use(s):** See the technical data sheet on this product for further information.

Product name: SYLGARD™ 3-6605 Thermally Conductive Revision Date: 18.10.2019
Elastomer Part B Version: 1.0

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value		
Methyltrimethoxysilane	ACGIH	TWA Respirable	1 mg/m3 , Aluminium		
treated aluminum oxide		fraction			
	Further information: LRT irr: Lower Respiratory Tract irritation; pneumoconiosis: Pneumoconiosis; neurotoxicity: Neurotoxicity; A4: Not classifiable as a human carcinogen; varies: varies				
	FR VLE	VME	10 mg/m3		
	Further information: normal	: Indicative exposure limits			
Methyl trimethoxysilane-	Dow IHG	TWA Respirable	0,2 mg/m3		
treated silica		fraction.			

## **Derived No Effect Level**

Dodecamethyl cyclohexasiloxane

## Workers

Acute syste	emic effects	Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	6,1 mg/m3	n.a.	11 mg/m3	n.a.	1,22 mg/m3

## Consumers

Acute systemic effects		Acute lo	cal effects	Long-term systemic effects		Long-term local effects			
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	1,7 mg/kg bw/day	n.a.	1,5 mg/m3	n.a.	2,7 mg/m3	1,7 mg/kg bw/day	n.a.	0,3 mg/m3

## Methyl trimethoxysilane-treated silica

## Workers

Acute syste	emic effects	Acute local effects		Long-term systemic effects		Long-term local effects	
Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	4 mg/m3	n.a.	n.a.

## **Consumers**

Acute systemic effects		Acute loc	cal effects	Long-term systemic effects		Long-term local effects			
Dermal	Inhalation	Oral	Dermal	Inhalation	Dermal	Inhalation	Oral	Dermal	Inhalation
n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.	n.a.

## **Predicted No Effect Concentration**

Dodecamethyl cyclohexasiloxane

Compartment	PNEC
Fresh water sediment	2,826 mg/kg
Marine sediment	0,282 mg/kg

Page 5 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

Soil	3,336 mg/kg
Sewage treatment plant	> 1,0 mg/l

#### 8.2 Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

#### Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

#### Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or quidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2 (meeting standard EN 14387).

## **Environmental exposure controls**

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

Page 6 of 18

Product name: SYLGARD™ 3-6605 Thermally Conductive Revision Date: 18.10.2019 Elastomer Part B Version: 1.0

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state viscous liquid

Color grey
Odor none

Odor ThresholdNo data availablepHNo data availableMelting point/rangeNo data availableFreezing pointNo data available

Boiling point (760 mmHg) > 100 °C

Flash point closed cup >101 °C
Evaporation Rate (Butyl Acetate No data available

= 1)

Flammability (solid, gas)

Flammability (liquids)

Lower explosion limit

Upper explosion limit

Vapor Pressure

Relative Vapor Density (air = 1)

Not applicable

Not applicable

No data available

No data available

Relative Density (water = 1) 2,1

Water solubility

No data available

Partition coefficient: n
No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data available

Dynamic Viscosity 500 poise

**Kinematic Viscosity**No data available **Explosive properties**Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

9.2 Other information

Molecular weightNo data availableParticle sizeNot applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## **SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:** Not classified as a reactivity hazard.

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

10.2 Chemical stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can react with strong oxidizing agents. Product may evolve flammable hydrogen gas on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air. Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid: Exposure to moisture

10.5 Incompatible materials: Oxidizing agents

#### 10.6 Hazardous decomposition products:

Decomposition products can include and are not limited to: Formaldehyde.

## SECTION 11: TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

#### 11.1 Information on toxicological effects

#### Information on likely routes of exposure

Inhalation, Eye contact, Skin contact, Ingestion.

Acute toxicity (represents short term exposures with immediate effects - no chronic/delayed effects known unless otherwise noted)

## Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. Signs and symptoms of excessive exposure may include: Gastrointestinal irritation.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5 000 mg/kg Estimated.

#### Information for components:

#### Dodecamethyl cyclohexasiloxane

LD50, Rat, male and female, > 2 000 mg/kg No deaths occurred at this concentration.

## Methyltrimethoxysilane treated aluminum oxide

LD50, Rat, > 5 000 mg/kg OECD Test Guideline 401

## Methyl trimethoxysilane-treated silica

Based on data from similar materials LD50, Rat, > 5 000 mg/kg

## Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Page 8 of 18

Elastomer Part B Version: 1.0

**Revision Date: 18.10.2019** 

Based on information for component(s): LD50, Rabbit, > 2 000 mg/kg Estimated.

#### Information for components:

#### **Dodecamethyl cyclohexasiloxane**

LD50, Rabbit, male and female, > 2 000 mg/kg

## Methyltrimethoxysilane treated aluminum oxide

The dermal LD50 has not been determined.

#### Methyl trimethoxysilane-treated silica

The dermal LD50 has not been determined.

#### Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

## Information for components:

#### Dodecamethyl cyclohexasiloxane

The LC50 has not been determined.

## Methyltrimethoxysilane treated aluminum oxide

For similar material(s): LC50, Rat, male and female, dust/mist, > 2,3 mg/l No deaths occurred at this concentration.

## Methyl trimethoxysilane-treated silica

The LC50 has not been determined.

## Skin corrosion/irritation

Based on information for component(s):

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause slight skin irritation with local redness.

## Information for components:

#### Dodecamethyl cyclohexasiloxane

Essentially nonirritating to skin.

#### Methyltrimethoxysilane treated aluminum oxide

Brief contact is essentially nonirritating to skin.

Mechanical injury only.

#### Methyl trimethoxysilane-treated silica

For similar material(s):

Brief contact is essentially nonirritating to skin.

## Serious eye damage/eye irritation

Based on information for component(s):

May cause slight temporary eye irritation.

Page 9 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

Corneal injury is unlikely.

## Information for components:

## **Dodecamethyl cyclohexasiloxane**

May cause slight temporary eye irritation. Corneal injury is unlikely.

## Methyltrimethoxysilane treated aluminum oxide

Solid or dust may cause irritation or corneal injury due to mechanical action.

#### Methyl trimethoxysilane-treated silica

For similar material(s):

May cause slight temporary eye irritation.

Corneal injury is unlikely.

#### Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

## Information for components:

## Dodecamethyl cyclohexasiloxane

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

## Methyltrimethoxysilane treated aluminum oxide

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

## Methyl trimethoxysilane-treated silica

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

## **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## Information for components:

#### **Dodecamethyl cyclohexasiloxane**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

## Methyltrimethoxysilane treated aluminum oxide

Page 10 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

### Methyl trimethoxysilane-treated silica

Available data are inadequate to determine single exposure specific target organ toxicity.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

#### Information for components:

## Dodecamethyl cyclohexasiloxane

Based on physical properties, not likely to be an aspiration hazard.

#### Methyltrimethoxysilane treated aluminum oxide

Based on physical properties, not likely to be an aspiration hazard.

### Methyl trimethoxysilane-treated silica

Based on physical properties, not likely to be an aspiration hazard.

Chronic toxicity (represents longer term exposures with repeated dose resulting in chronic/delayed effects - no immediate effects known unless otherwise noted)

#### Specific Target Organ Systemic Toxicity (Repeated Exposure)

Repeated excessive exposures to alumina (aluminium oxide) dust or fumes may cause respiratory effects.

Exposure to alumina alone has not been shown to cause chronic lung disease. Some forms of alumina, when injected directly into the lungs of animals, caused fibrosis, but this is an abnormal route of exposure.

## Information for components:

#### Dodecamethyl cyclohexasiloxane

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

#### Methyltrimethoxysilane treated aluminum oxide

Repeated excessive exposures to alumina (aluminium oxide) dust or fumes may cause respiratory effects.

Exposure to alumina alone has not been shown to cause chronic lung disease. Some forms of alumina, when injected directly into the lungs of animals, caused fibrosis, but this is an abnormal route of exposure.

#### Methyl trimethoxysilane-treated silica

No relevant data found.

## Carcinogenicity

No relevant data found.

#### Information for components:

#### Dodecamethyl cyclohexasiloxane

No relevant data found.

Page 11 of 18

Elastomer Part B Version: 1.0

**Revision Date: 18.10.2019** 

#### Methyltrimethoxysilane treated aluminum oxide

Although certain forms of alumina have been reported to induce tumors when injected directly into the lungs of laboratory animals, there is no evidence that alumina is carcinogenic under normal routes of exposure.

#### Methyl trimethoxysilane-treated silica

No relevant data found.

## **Teratogenicity**

High doses of aluminium and aluminium salts given to laboratory animals during pregnancy have caused developmental toxicity in the fetus at doses mildly toxic to the mother. The relevance of these data to alumina is unknown.

#### Information for components:

#### Dodecamethyl cyclohexasiloxane

No relevant data found.

## Methyltrimethoxysilane treated aluminum oxide

High doses of aluminium and aluminium salts given to laboratory animals during pregnancy have caused developmental toxicity in the fetus at doses mildly toxic to the mother. The relevance of these data to alumina is unknown.

#### Methyl trimethoxysilane-treated silica

No relevant data found.

#### Reproductive toxicity

No relevant data found.

## Information for components:

#### Dodecamethyl cyclohexasiloxane

No relevant data found.

#### Methyltrimethoxysilane treated aluminum oxide

No relevant data found.

## Methyl trimethoxysilane-treated silica

No relevant data found.

## Mutagenicity

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Contains component(s) which were negative in some animal genetic toxicity studies and positive in others.

#### Information for components:

#### <u>Dodecamethyl cyclohexasiloxane</u>

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

## Methyltrimethoxysilane treated aluminum oxide

Page 12 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

For similar material(s): In vitro genetic toxicity studies were negative in some cases and positive in other cases. Animal genetic toxicity studies were negative in some cases and positive in other cases.

#### Methyl trimethoxysilane-treated silica

For similar material(s): In vitro genetic toxicity studies were negative.

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological information appears in this section when such data is available.

#### 12.1 Toxicity

## Dodecamethyl cyclohexasiloxane

## Acute toxicity to algae/aquatic plants

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 0,002 mg/l

### Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, Daphnia magna (Water flea), 21 d, 0,0046 mg/l

## Methyltrimethoxysilane treated aluminum oxide

## Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

EC50, Fish, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

## Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

## Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 100 mg/l, OECD Test Guideline 201 or Equivalent

#### Methyl trimethoxysilane-treated silica

#### Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on data from similar materials

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l

## Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

#### Acute toxicity to algae/aguatic plants

Based on data from similar materials

Page 13 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

EC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, > 100 mg/l Based on data from similar materials

NOEC, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, 100 mg/l

## 12.2 Persistence and degradability

#### Dodecamethyl cyclohexasiloxane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 57 % Exposure time: 28 d

Method: OECD Test Guideline 301B

#### Methyltrimethoxysilane treated aluminum oxide

Biodegradability: Biodegradation is not applicable.

## Methyl trimethoxysilane-treated silica

Biodegradability: No relevant data found.

#### 12.3 Bioaccumulative potential

#### Dodecamethyl cyclohexasiloxane

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater

Partition coefficient: n-octanol/water(log Pow): 8,87

#### Methyltrimethoxysilane treated aluminum oxide

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

#### Methyl trimethoxysilane-treated silica

Bioaccumulation: No relevant data found.

#### 12.4 Mobility in soil

#### Dodecamethyl cyclohexasiloxane

Potential for mobility in soil is very high (Koc between 0 and 50).

#### Methyltrimethoxysilane treated aluminum oxide

No relevant data found.

#### Methyl trimethoxysilane-treated silica

No relevant data found.

#### 12.5 Results of PBT and vPvB assessment

#### <u>Dodecamethyl cyclohexasiloxane</u>

Dodecamethyl cyclohexasiloxane (D6) meets the current REACh Annex XIII criteria for vPvB. However, D6 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D6 is not biomagnifying in aquatic and terrestrial food webs. D6 in air will degrade by reaction with naturally occurring hydroxyl

Page 14 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

radicals in the atmosphere. Any D6 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

## Methyltrimethoxysilane treated aluminum oxide

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

#### Methyl trimethoxysilane-treated silica

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

#### 12.6 Other adverse effects

#### Dodecamethyl cyclohexasiloxane

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### Methyltrimethoxysilane treated aluminum oxide

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

#### Methyl trimethoxysilane-treated silica

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods

Do not dump into any sewers, on the ground, or into any body of water. This product, when being disposed of in its unused and uncontaminated state should be treated as a hazardous waste according to EC Directive 2008/98/EC. Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

## **SECTION 14: TRANSPORT INFORMATION**

## Classification for ROAD and Rail transport (ADR/RID):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

14.3 Transport hazard class(es) Not applicable 14.4 Packing group Not applicable

14.5 Environmental hazards Not considered environmentally hazardous based on

available data.

**14.6** Special precautions for user No data available.

## Classification for SEA transport (IMO-IMDG):

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport

Page 15 of 18

Product name: SYLGARD™ 3-6605 Thermally Conductive Revision Date: 18.10.2019
Elastomer Part B Version: 1.0

14.3 Transport hazard class(es) Not applicable14.4 Packing group Not applicable

**14.5 Environmental hazards** Not considered as marine pollutant based on available data.

14.6 Special precautions for user No data available.

14.7 Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Consult IMO regulations before transporting ocean bulk

## Classification for AIR transport (IATA/ICAO):

**14.1 UN number** Not applicable

**14.2 UN proper shipping name** Not regulated for transport

14.3 Transport hazard class(es) Not applicable
 14.4 Packing group Not applicable
 14.5 Environmental hazards Not applicable
 14.6 Special precautions for user No data available.

#### Further information:

VENTED PACKAGES ARE FORBIDDEN FOR AIR TRANSPORT.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

#### **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### REACh Regulation (EC) No 1907/2006

This product contains only components that have been either registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

#### **Authorisation status under REACH:**

The following substance/s contained in this product might be or is/are subject to authorization in accordance with REACH:

Elastomer Part B Version: 1.0

**Revision Date: 18.10.2019** 

CAS-No.: 540-97-6 Name: Dodecamethyl cyclohexasiloxane

Authorisation status: listed in the Candidate List of Substances of Very High Concern for Authorisation

Authorisation number: Not available

Sunset date: Not available

Exempted (Categories of) Uses: Not available

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: Not applicable

Installations classified for the protection of the environment (Environment Code R511-9)

not determined

Occupational Illnesses (R-461-3, France): (Not applicable)

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture.

#### **SECTION 16: OTHER INFORMATION**

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

This product is not classified as dangerous according to EC criteria.

#### Revision

Identification Number: 4059646 / A560 / Issue Date: 18.10.2019 / Version: 1.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

aocumeni

## Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline
FR VLE	France. Occupational Exposure Limits (INRS)
TWA	Time weighted average
VME	Time Weighted Average

#### Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good

Page 17 of 18

**Revision Date: 18.10.2019 Elastomer Part B** Version: 1.0

Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China: IMDG -International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW FRANCE S.A.S. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version. FR

Page 18 of 18