

SIMSON Prep G plus

PREPARATION AGENT

KEY BENEFITS

- UV blocking
- Can replace ceramic coating
- Glossy surface after curing

DESCRIPTION

Simson Prep G plus is a black primer specifically designed for the ceramic band on vehicle glass. It ensures the complete protection of the adhesive by creating a barrier against harmful UV rays, which can lead to the degradation of the adhesive. It is also an adhesion promoter. To be used in conjunction with Bostik Cleaner I or Bostik Cleaner 9.

APPLICATION

Pretreatment of glass substrates with ceramic coating.

METHOD OF USE

The surfaces to be treated must be perfectly clean, dry, dust and grease free.

Application of Prep G plus can only take place once the thorough cleaning of the bonding area with Cleaner I (or equivalent) has been completed. Shake bottle well before application (for at least 1 min.) till the noise of the metal balls contained in the bottle can be heard. Apply product using a felt applicator. Close immediately after use as the product evaporates very quickly. Ensure that the primer is tack-free dry before proceeding.

PACKAGING

For existing packaging sizes, please call your Bostik sales representative.

STORAGE STABILITY

Simson Prep G plus can be stored for at least 12 months from date of manufacture when stored in original unopened container in a dry place within the temperature range +5°C to +25°C.

TECHNICAL DATA

CHARACTERISTIC		VALUE
Aspect		liquid
Curing mechanism		moisture curing
Specific gravity	[gr/cc]	0,95
Minimum drying time 23°C/50% R.H.	[min]	3
Maximum drying time 23°C/50% R.H.	[min]	24h
Application temperature	[°C]	+5 to +30
Colour		Black

FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

