

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® MY 740

REACH Registration Number : 01-2119456619-26

Substance name : 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE
(PREVIOUSLY: BISPENOL A EPOXY RESIN (MW<700))

CAS-No. : 1675-54-3

Index-No. : 603-074-00-8

EC-No. : 216-823-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Component used for the manufacture of electrical insulation parts

ES1: Formulation
ES2: Used as monomer at downstream industrial sites
ES3: Used as chemical intermediate
ES4: Industrial use
ES5: Professional
ES6: Consumer application of coatings

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium

Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : Centres Antipoison et de Toxicovigilance:
ANGERS: 02 41 48 21 21
BORDEAUX: 05 56 96 40 80
LILLE: 0 825 812 822
LYON: 04 72 11 69 11
MARSEILLE 04 91 75 25 25
NANCY: 03 83 32 36 36
PARIS: 01 40 05 48 48
RENNES: 02 99 59 22 22
STRASBOURG: 03 88 37 37 37
TOULOUSE: 05 61 77 74 47
EUROPE: +32 35 75 1234

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P391 Collect spillage.

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : 2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE
(PREVIOUSLY: BISPHENOL A EPOXY RESIN (MW<700))

Index-No. : 603-074-00-8

EC-No. : 216-823-5

Hazardous components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5	>= 90 - <= 100

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon oxides
Halogenated compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Further information on storage stability : Stable under normal conditions.

Recommended storage temperature : 2 - 40 °C

7.3 Specific end use(s)

Specific use(s) : See Annex to the Safety data sheet for additional information in the Exposure Scenario(s).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740Version
1.0Revision Date:
12.09.2019SDS Number:
400001000051Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8,33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12,25 mg/m ³
	Workers	Dermal	Systemic effects, Long-term exposure	8,33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12,25 mg/m ³
	Consumers	Dermal	Systemic effects, Short-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	0,75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3,571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0,75 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value	
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0,006 mg/l	
	Remarks:	Assessment Factors	
		Marine water	0,0006 mg/l
		Assessment Factors	
		Freshwater - intermittent	0,018 mg/l
		Assessment Factors	
		Fresh water sediment	0,996 mg/kg
		Equilibrium method	
		Marine sediment	0,0996 mg/kg
		Equilibrium method	
		Soil	0,196 mg/kg
		Equilibrium method	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

	Sewage treatment plant	10 mg/l
Assessment Factors		
	Secondary Poisoning	11 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene gloves
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : ca. 7 (20 °C)
Concentration: 500 g/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

Freezing point	:	No data is available on the product itself.
Melting point	:	No data is available on the product itself.
Boiling point	:	> 200 °C
Flash point	:	> 200 °C Method: Pensky-Martens closed cup, closed cup
Evaporation rate	:	No data is available on the product itself.
Flammability (solid, gas)	:	No data is available on the product itself.
Burning rate	:	No data is available on the product itself.
Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	< 0,0001 hPa (20 °C)
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	1,15 - 1,2 g/cm ³ (25 °C)
Solubility(ies)	:	
Water solubility	:	practically insoluble (20 °C)
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Auto-ignition temperature	:	No data is available on the product itself.
Decomposition temperature	:	> 200 °C
Viscosity	:	
Viscosity, dynamic	:	10 000 - 14 500 mPa.s (25 °C)
Explosive properties	:	No data is available on the product itself.
Oxidizing properties	:	No data is available on the product itself.

9.2 Other information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2 000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2 000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rabbit
Assessment: Mild skin irritant
Method: OECD Test Guideline 404
Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rabbit
Assessment: Mild eye irritant
Method: OECD Test Guideline 405
Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429
Result: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

: Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: >750 milligram per kilogram

General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight

General Toxicity F1: No-observed-effect level: 540 mg/kg body weight

Symptoms: No adverse effects

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: Ingestion
Exposure time: 14 Weeks Number of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female
NOEL: 10 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks Number of exposures: 5 d
Method: Subchronic toxicity

Species: Mouse, male
NOAEL: 100 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks Number of exposures: 3 d
Method: Subchronic toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1,5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2,7 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

aquatic invertebrates Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 9,4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4,83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7,1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3,58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

Partition coefficient: n-octanol/water : log Pow: 3,242 (25 °C)
pH: 7,1
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number : UN 3082

14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
EmS Code : F-A, S-F
14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 3082
14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN)
14.3 Transport hazard class(es) : 9
14.4 Packing group : III
Labels : 9
14.5 Environmental hazards
Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Occupational Illnesses (R-461-3, France) : 51

Installations classified for the protection of the environment (Environment Code R511-9) : 4511

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

For further information see eSDS.

SECTION 16: Other information

Further information

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Annex to the Safety Data Sheet (eSDS)

ES 1	Formulation; Formulation [mixing] of preparations and/ or re-packaging (excluding alloys) (SU 10).
ES 2	Used as monomer at downstream industrial sites; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
ES 3	Used as chemical intermediateIntermediate (PC19); Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
ES 4	Industrial use; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
ES 5	Professional; Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22).
ES 6	Consumer application of coatingsAdhesives, sealants (PC1); Consumer uses (SU21).Coatings and paints, thinners, paint removers (PC9a); Consumer uses (SU21).Fillers, putties, plasters, modelling clay (PC9b); Consumer uses (SU21).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 1: ; Formulation [mixing] of preparations and/ or re-packaging (excluding alloys) (SU 10).

1.1. Title section

Exposure Scenario name	: Formulation
Structured Short Title	: ; Formulation [mixing] of preparations and/ or re-packaging (excluding alloys) (SU 10).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Formulation of preparations	ERC2
Worker		
CSCS 2	Use in closed batch process (synthesis or formulation)	PROC3
CSCS 3	Use in batch and other process (synthesis) where opportunity for exposure arises	PROC4
CSCS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CSCS 5	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: Formulation of preparations (ERC2)

Product (article) characteristics	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount per use	: 116421 tonnes/year
Fraction of EU tonnage used in region:	: 0,1
Fraction of regional tonnage used locally	: 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Msporc	:	32339 kg/d
Conditions and measures related to sewage treatment plant		
STP type	:	Municipal sewage treatment plant
STP effluent	:	2 000 m3/d
Conditions and measures related to treatment of waste (including article waste)		
Waste treatment	:	Waste gases incinerated.
Waste - minimum efficiency of	:	95 %
Other conditions affecting environmental exposure		
Receiving surface water flow	:	18 000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

1.2.2. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics		
Covers percentage substance in the product up to 100 %.		
Physical form of product	:	Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	:	Covers daily exposures up to 8 hours
Technical and organisational conditions and measures		
No other specific measures identified.		
Assumes a good basic standard of occupational hygiene is implemented		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear suitable gloves tested to EN374.		
Other conditions affecting workers exposure		
Indoor or outdoor use	:	Indoor
Temperature	:	> 70 °C

1.2.3. Control of worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

Product (article) characteristics
--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified.	
Assumes a good basic standard of occupational hygiene is implemented	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Professional or industrial settings	: Industrial use
Temperature	: > 70 °C

1.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

1.2.5. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Liquid substance
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes process temperature up to < 70 °C

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: Formulation of preparations (ERC2)

Release route	Release rate	Release estimation method
Water	0 kg/day	FEICA SPERC 2.1b.v1
Air	9,7 kg/day	FEICA SPERC 2.1b.v1
Soil	0 kg/day	FEICA SPERC 2.1b.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	0mg/L (ECETOC TRA environment v2.0)	0
Freshwater	1.06E-06 mg/Lmg/L (ECETOC TRA environment v2.0)	1.76E-04
Freshwater sediment	5.75E-05 mg/kg dwmg/kg dry weight (ECETOC TRA environment v2.0)	5.77E-05
Soil	0,244mg/kg dry weight (ECETOC TRA environment v2.0)	0,662

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Marine water	8.36E-09 mg/Lmg/L (ECETOC TRA environment v2.0)	1.39E-05
Marine sediment	4.55E-07 mg/kg dwmg/kg dry weight (ECETOC TRA environment v2.0)	4.56E-06

1.3.2. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,138mg/kg bw/day (ECETOC TRA worker v2.0)	0,02
combined routes			(ECETOC TRA worker v2.0)	0,07

1.3.3. Worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,686mg/kg bw/day (ECETOC TRA worker v2.0)	0,08
combined routes			(ECETOC TRA worker v2.0)	0,13

1.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,1mg/m ³ (ECETOC TRA worker v2.0)	0,01
dermal	systemic	long-term	0.06855mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes			(ECETOC TRA worker v2.0)	0,02

1.3.5. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
----------------	---------------	--------------------	-------------------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,686mg/kg bw/day (ECETOC TRA worker v2.0)	0,08
combined routes			(ECETOC TRA worker v2.0)	0,13

1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 2: ; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).

2.1. Title section

Exposure Scenario name	: Used as monomer at downstream industrial sites
Structured Short Title	: ; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CSCS 2	Use in closed process, no likelihood of exposure	PROC1
CSCS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CSCS 4	Use in closed batch process (synthesis or formulation)	PROC3
CSCS 5	Bulk transfers	PROC8b

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Amount per use	: 75303 tonnes/year
Fraction of EU tonnage used in region:	: 0,25
Msperc	: 62753 kg/d
Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2 000 m3/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Liquid and/or solid waste is treated by incineration.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18 000 m ³ /d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

2.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

2.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

2.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

2.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Release route	Release rate	Release estimation method
Water	3.77E-02kg/day	ESVOC SPERC 4.20.v1
Air	2,51 kg/day	ESVOC SPERC 4.20.v1
Soil		ESVOC SPERC 4.20.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	0,0177mg/L (ECETOC TRA environment v2.0)	1.77E-03
Freshwater	0,00177mg/L (ECETOC TRA environment v2.0)	2.95E-03
Freshwater sediment	0,0963mg/kg dry weight (ECETOC TRA environment v2.0)	9.67e-02
Soil	0,0529mg/kg dry weight (ECETOC TRA environment v2.0)	1.45E-01
Marine water	0,000188mg/L (ECETOC TRA environment v2.0)	3.14E-01
Marine sediment	0,0102mg/kg dry weight (ECETOC TRA environment v2.0)	1.03E-01

2.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,006mg/kg bw/day	0,001

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version
1.0

Revision Date:
12.09.2019

SDS Number:
400001000051

Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

			(ECETOC TRA worker v2.0)	
combined routes			(ECETOC TRA worker v2.0)	0,05

2.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,43ppm (ECETOC TRA worker v2.0)	0,03
dermal	systemic	long-term	0,274mg/kg bw/day (ECETOC TRA worker v2.0)	0,03
combined routes			(ECETOC TRA worker v2.0)	0,07

2.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64mg/m ³ (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,138mg/kg bw/day (ECETOC TRA worker v2.0)	0,02
combined routes			(ECETOC TRA worker v2.0)	0,07

2.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,7mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	1,371mg/kg bw/day (ECETOC TRA worker v2.0)	0,16
combined routes			(ECETOC TRA worker v2.0)	0,22

2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 3: Intermediate (PC19); Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).

3.1. Title section

Exposure Scenario name	: Used as chemical intermediate
Structured Short Title	: Intermediate (PC19); Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Use as an intermediate	ERC6a
Worker		
CSCS 2	Use in closed process, no likelihood of exposure	PROC1
CSCS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CSCS 4	Use in closed batch process (synthesis or formulation)	PROC3
CSCS 5	Bulk transfers	PROC8b

3.2. Conditions of use affecting exposure

3.2.1. Control of environmental exposure: Industrial use resulting in manufacture of another substance (use of intermediates) (ERC6a)

Product (article) characteristics	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 10125 tonnes/day
Fraction of EU tonnage used in region:	: 0,25
Fraction of regional tonnage used locally	: 1
Msperc	: 8438 kg/d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Conditions and measures related to sewage treatment plant	
STP type	: Municipal sewage treatment plant
STP effluent	: 2 000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Do not apply industrial sludge to natural soils.
Waste treatment	: Liquid and/or solid waste is treated by incineration.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18 000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

3.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

3.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

3.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

3.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

3.3. Exposure estimation and reference to its source

3.3.1. Environmental release and exposure: Industrial use resulting in manufacture of another substance (use of intermediates) (ERC6a)

Release route	Release rate	Release estimation method
Water	5.06E-03kg/day	ESVOC SPERC 6.1a.v1
Air	0 kg/day	ESVOC SPERC 6.1a.v1
Soil		ESVOC SPERC 6.1a.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	2.38E-03mg/L (ECETOC TRA environment v2.0)	2.38E-04
Freshwater	2.39E-04mg/L (ECETOC TRA environment v2.0)	3.98E-02
Freshwater sediment	1.30E-02mg/kg dry weight (ECETOC TRA environment v2.0)	1.30E-02
Soil	4.61E-04mg/kg dry weight (ECETOC TRA environment v2.0)	2.35E-03
Marine water	2.53E-05mg/L (ECETOC TRA environment v2.0)	4.22E-02

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Marine sediment	1.38E-05mg/kg dry weight (ECETOC TRA environment v2.0)	1.38E-02
-----------------	---	----------

3.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,14ppm (ECETOC TRA worker v2.0)	0,01
dermal	systemic	long-term	0,006mg/kg bw/day (ECETOC TRA worker v2.0)	0,001
combined routes			(ECETOC TRA worker v2.0)	0,01

3.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,43ppm (ECETOC TRA worker v2.0)	0,03
dermal	systemic	long-term	0,274mg/kg bw/day (ECETOC TRA worker v2.0)	0,03
combined routes			(ECETOC TRA worker v2.0)	0,07

3.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,138mg/kg bw/day (ECETOC TRA worker v2.0)	0,02
combined routes			(ECETOC TRA worker v2.0)	0,07

3.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,7ppm (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	1,371mg/kg bw/day (ECETOC TRA worker v2.0)	0,16

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

combined routes			(ECETOC TRA worker v2.0)	0,22
-----------------	--	--	--------------------------	------

3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 4: ; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).

4.1. Title section

Exposure Scenario name	: Industrial use
Structured Short Title	: ; Industrial uses: Uses of substances as such or in preparations at industrial sites (SU 3).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Industrial use	ERC5
Worker		
CSCS 2	Spraying	PROC7
CSCS 3	Material transfers	PROC8b
CSCS 4	Rolling, Brushing	PROC10
CSCS 5	Dipping, immersion and pouring	PROC13
CSCS 6	Laboratory activities	PROC15

4.2. Conditions of use affecting exposure

4.2.1. Control of environmental exposure: Use at industrial site leading to inclusion into/onto article (ERC5)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 40139 tonnes/day
Fraction of EU tonnage used in region:	: 0,25

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Mspc	:	33449 kg/day
Conditions and measures related to sewage treatment plant		
STP type	:	Municipal sewage treatment plant
STP effluent	:	2 000 m3/d
Other conditions affecting environmental exposure		
Receiving surface water flow	:	18 000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

4.2.2. Control of worker exposure: Industrial spraying (PROC7)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear respiratory protection when its use is identified for certain contributing scenarios.	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

4.2.3. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

4.2.4. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

4.2.5. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear suitable gloves tested to EN374.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: > 70 °C

4.2.6. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: < 40 °C

4.3. Exposure estimation and reference to its source

4.3.1. Environmental release and exposure: Use at industrial site leading to inclusion into/onto article (ERC5)

Release route	Release rate	Release estimation method
Water	0 kg/day	FEICA SPERC 5.1a.v1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Air	2.16E-03kg/day	FEICA SPERC 5.1a.v1
Soil		FEICA SPERC 5.1a.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	0mg/L (ECETOC TRA environment v2.0)	0
Freshwater	1.06E-06mg/L (ECETOC TRA environment v2.0)	1.76E-04
Freshwater sediment	5.75E-05mg/kg dry weight (ECETOC TRA environment v2.0)	5.77E-05
Soil	6.34E-02mg/kg dry weight (ECETOC TRA environment v2.0)	1.73E-01
Marine water	8.36E-09mg/L (ECETOC TRA environment v2.0)	1.39E-05
Marine sediment	4.55E-07mg/kg dry weight (ECETOC TRA environment v2.0)	4.56E-06

4.3.2. Worker exposure: Industrial spraying (PROC7)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,14mg/m ³ (ECETOC TRA worker v2.0)	0,01
dermal	systemic	long-term	0,429mg/kg bw/day (ECETOC TRA worker v2.0)	0,05
combined routes			(ECETOC TRA worker v2.0)	0,06

4.3.3. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,7mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	1,371mg/kg bw/day (ECETOC TRA worker v2.0)	0,16
combined routes			(ECETOC TRA worker v2.0)	0,22

4.3.4. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure	Exposure	RCR
----------------	---------------	----------	----------	-----

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version
1.0

Revision Date:
12.09.2019

SDS Number:
400001000051

Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

		indicator	estimate	
inhalative	systemic	long-term	0.00045mg/m ³ (ECETOC TRA worker v2.0)	< 0,001
dermal	systemic	long-term	2,743mg/kg bw/day (ECETOC TRA worker v2.0)	0,33
combined routes			(ECETOC TRA worker v2.0)	0,33

4.3.5. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,64ppm (ECETOC TRA worker v2.0)	0,05
dermal	systemic	long-term	0,274mg/kg bw/day (ECETOC TRA worker v2.0)	0,03
combined routes			(ECETOC TRA worker v2.0)	0,09

4.3.6. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.000006mg/m ³ (ECETOC TRA worker v2.0)	< 0,001
dermal	systemic	long-term	0,07mg/kg bw/day (ECETOC TRA worker v2.0)	0,01
combined routes			(ECETOC TRA worker v2.0)	0,01

4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 5: ; Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22).

5.1. Title section

Exposure Scenario name	: Professional
Structured Short Title	: ; Professional uses: Public domain (administration, education, entertainment, services, craftsmen) (SU 22).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Wide dispersive indoor use resulting in inclusion into or onto a matrix	ERC8c
Worker		
CSCS 2	Drum/batch transfers	PROC8a
CSCS 3	Material transfers	PROC8b
CSCS 4	Rolling, Brushing	PROC10
CSCS 5	Spraying	PROC11
CSCS 6	Dipping, immersion and pouring	PROC13
CSCS 7	Hand-mixing with intimate contact and only PPE available	PROC19

5.2. Conditions of use affecting exposure

5.2.1. Control of environmental exposure: Wide dispersive indoor use resulting in inclusion into or onto a matrix (ERC8c)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount per use	: 47526 tonnes/year

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Wide dispersive use	:	
Conditions and measures related to sewage treatment plant		
STP type	:	Municipal sewage treatment plant
STP effluent	:	2 000 m3/d
Other conditions affecting environmental exposure		
Receiving surface water flow	:	18 000 m3/d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100

5.2.2. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Product (article) characteristics		
Covers percentage substance in the product up to 100 %.		
Physical form of product	:	Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure		
Duration	:	Covers exposure up to 4 hrs
Technical and organisational conditions and measures		
Avoid carrying out activities involving exposure for more than 4 hours per day. Assumes a good basic standard of occupational hygiene is implemented		
Conditions and measures related to personal protection, hygiene and health evaluation		
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.		
Other conditions affecting workers exposure		
Indoor or outdoor use	:	Indoor
Professional or industrial settings	:	Professional use
Temperature	:	Assumes use at not more than 20°C above ambient temperature.

5.2.3. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Product (article) characteristics		
Covers percentage substance in the product up to 100 %.		
Physical form of product	:	Low volatile liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
No other specific measures identified. Assumes a good basic standard of occupational hygiene is implemented	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes use at not more than 20°C above ambient temperature.

5.2.4. Control of worker exposure: Roller application or brushing (PROC10)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes use at not more than 20°C above ambient temperature.

5.2.5. Control of worker exposure: Non industrial spraying (PROC11)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Avoid using product more than 4 hrs
Technical and organisational conditions and measures	
Avoid carrying out activities involving exposure for more than 4 hours per day.	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes use at not more than 20°C above ambient temperature.

5.2.6. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes use at not more than 20°C above ambient temperature.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

5.2.7. Control of worker exposure: Hand-mixing with intimate contact and only PPE available (PROC19)

Product (article) characteristics	
Covers percentage substance in the product up to 100 %.	
Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Avoid carrying out activities involving exposure for more than 1 hrs
Technical and organisational conditions and measures	
Assumes a good basic standard of occupational hygiene is implemented	
Avoid carrying out activities involving exposure for more than 4 hours per day.	
No other specific measures identified.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor
Temperature	: Assumes use at not more than 20°C above ambient temperature.

5.3. Exposure estimation and reference to its source

5.3.1. Environmental release and exposure: Wide dispersive indoor use resulting in inclusion into or onto a matrix (ERC8c)

Release route	Release rate	Release estimation method
Water	4.69E-03kg/day	FEICA SPERC 8c.1b.v1
Air	0 kg/day	FEICA SPERC 8c.1b.v1
Soil	0 kg/day	FEICA SPERC 8c.1b.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	2.20E-03mg/L (ECETOC TRA environment v2.0)	2.20E-04
Freshwater	2.21E-04mg/L (ECETOC TRA environment v2.0)	3.69E-02
Freshwater sediment	1.20E-02mg/kg dry weight (ECETOC TRA environment v2.0)	1.21E-02

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Soil	1.42E-03mg/kg dry weight (ECETOC TRA environment v2.0)	7.22E-03
Marine water	2.34E-05mg/L (ECETOC TRA environment v2.0)	2.90E-02
Marine sediment	1.27E-03mg/kg dry weight (ECETOC TRA environment v2.0)	1.28E-02

5.3.2. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,84mg/m ³ (ECETOC TRA worker v2.0)	0,07
dermal	systemic	long-term	0,274mg/kg bw/day (ECETOC TRA worker v2.0)	0,03
combined routes			(ECETOC TRA worker v2.0)	0,10

5.3.3. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,7mg/m ³ (ECETOC TRA worker v2.0)	0,06
dermal	systemic	long-term	0,273mg/kg bw/day (ECETOC TRA worker v2.0)	0,03
combined routes			(ECETOC TRA worker v2.0)	0,09

5.3.4. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.00000005mg/m ³ (ECETOC TRA worker v2.0)	< 0,001
dermal	systemic	long-term	2,743mg/kg bw/day (ECETOC TRA worker v2.0)	0,33
combined routes			(ECETOC TRA worker v2.0)	0,33

5.3.5. Worker exposure: Non industrial spraying (PROC11)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0,36mg/m ³ (ECETOC TRA worker v2.0)	0,03
dermal	systemic	long-term	2,68mg/kg bw/day (ECETOC TRA worker v2.0)	0,32
combined routes			(ECETOC TRA worker v2.0)	0,35

5.3.6. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.000006ppm (ECETOC TRA worker v2.0)	< 0,001
dermal	systemic	long-term	1,371mg/kg bw/day (ECETOC TRA worker v2.0)	0,16
combined routes			(ECETOC TRA worker v2.0)	0,16

5.3.7. Worker exposure: Hand-mixing with intimate contact and only PPE available (PROC19)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.00000002mg/m ³ (ECETOC TRA worker v2.0)	< 0,001
dermal	systemic	long-term	1,41mg/kg bw/day (ECETOC TRA worker v2.0)	0,42
combined routes			(ECETOC TRA worker v2.0)	0,42

5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

ES 6: Adhesives, sealants (PC1); Consumer uses (SU21).Coatings and paints, thinners, paint removers (PC9a); Consumer uses (SU21).Fillers, putties, plasters, modelling clay (PC9b); Consumer uses (SU21).

6.1. Title section

Exposure Scenario name	: Consumer application of coatings
Structured Short Title	: Adhesives, sealants (PC1); Consumer uses (SU21).Coatings and paints, thinners, paint removers (PC9a); Consumer uses (SU21).Fillers, putties, plasters, modelling clay (PC9b); Consumer uses (SU21).
Substance	: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane <u>EC-No.:</u> 216-823-5 <u>Registration number:</u> 01-2119456619-26

Environment		
CS 1	Wide dispersive indoor use resulting in inclusion into or onto a matrix, Wide dispersive outdoor use resulting in inclusion into or onto a matrix	ERC8c, ERC8f
Consumer		
CS 2	Two component glue, Mixing and loading	PC1
CS 3	Two component glue, Application	PC1
CS 4	Coatings and paints, thinners, paint removers, Mixing and loading	PC9a
CS 5	Coatings and paints, thinners, paint removers, Application	PC9a
CS 6	Fillers, putties, plasters, modelling clay, Mixing and loading	PC9b
CS 7	Fillers, putties, plasters, modelling clay, Application	PC9b

6.2. Conditions of use affecting exposure

6.2.1. Control of environmental exposure: Wide dispersive indoor use resulting in inclusion into or onto a matrix (ERC8c) / Wide dispersive outdoor use resulting in inclusion into or onto a matrix (ERC8f)

Product (article) characteristics
Covers percentage substance in the product up to 100 %.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Physical form of product	: Low volatile liquid
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount used in the EU	: 1667 tonnes/year
Wide dispersive use	:
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18 000 m ³ /d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100

6.2.2. Control of consumer exposure: Adhesives, sealants (PC1)

Product (article) characteristics	
Covers concentrations up to 45 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure
Amount used (or contained in articles), frequency and duration of use/exposure	
Amount per use	: 20 g
Use frequency	: Use frequency 3 times per year
Conditions and measures related to personal protection, hygiene and health evaluation	
No specific measures identified.	
Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to fingertips.
Indoor or outdoor use	: Indoor use
Room size	: Assumes a room volume of maximum 20 m ³
Temperature	: 20 °C

6.2.3. Control of consumer exposure: Adhesives, sealants (PC1)

Product (article) characteristics	
Covers concentrations up to 12,25 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Amount used (or contained in articles), frequency and duration of use/exposure	
Amounts used	: 20 g
Use frequency	: Use frequency 3 times per year
Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to fingertips.
Indoor or outdoor use	: Indoor use
Room size	: Covers use in room size of 20 m ³
Temperature	: 20 °C

6.2.4. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Product (article) characteristics	
Covers concentrations up to 35 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure
Amount used (or contained in articles), frequency and duration of use/exposure	
For each use event, covers use amounts up to	: 2250 g
Use frequency	: Use frequency 0,33 times per year
Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to fingertips.
Indoor or outdoor use	: Indoor use
Temperature	: 20 °C

6.2.5. Control of consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Product (article) characteristics	
Covers concentrations up to 12,25 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure
Amount used (or contained in articles), frequency and duration of use/exposure	
For each use event, covers use amounts up to	: 2250 g

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Use frequency	: Use frequency 0,33 times per year
Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to hands.
Indoor or outdoor use	: Indoor use
Room size	: 20 m ³
Temperature	: 20 °C

6.2.6. Control of consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Product (article) characteristics	
Covers concentrations up to 45 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure
Amount used (or contained in articles), frequency and duration of use/exposure	
For each use event, covers use amounts up to	: 200 g
Use frequency	: Use frequency 2 times per year
Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to fingertips.
Indoor or outdoor use	: Indoor use
Room size	: 20 m ³
Temperature	: 20 °C

6.2.7. Control of consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Product (article) characteristics	
Covers concentrations up to 45 %	
Physical form of product	: Liquid substance
Vapour pressure	: Vapour pressure < 0.01 Pa at standard temperature and pressure
Amount used (or contained in articles), frequency and duration of use/exposure	
For each use event, covers use amounts up to	: 200 g
Use frequency	: Use frequency 2 times per year

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version 1.0 Revision Date: 12.09.2019 SDS Number: 400001000051 Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Other conditions affecting consumers exposure	
Body parts exposed	: Assumes that potential dermal contact is limited to fingertips.
Indoor or outdoor use	: Indoor use
Room size	: 20 m ³
Temperature	: 20 °C

6.3. Exposure estimation and reference to its source

6.3.1. Environmental release and exposure: Wide dispersive indoor use resulting in inclusion into or onto a matrix (ERC8c) / Wide dispersive outdoor use resulting in inclusion into or onto a matrix (ERC8f)

Release route	Release rate	Release estimation method
Water	8.22E-03kg/day	FEICA SPERC 8c.1b.v1
Air	0 kg/day	FEICA SPERC 8c.1b.v1
Soil		FEICA SPERC 8c.1b.v1

Protection Target	Exposure estimate	RCR
Sewage treatment plant	3.87E-03mg/L (ECETOC TRA environment v2.0)	3.87E-04
Freshwater	3.87E-04mg/L (ECETOC TRA environment v2.0)	6.46E-02
Freshwater sediment	2.11E-02mg/kg dry weight (ECETOC TRA environment v2.0)	2.12E-02
Soil	2.14E-03mg/kg dry weight (ECETOC TRA environment v2.0)	1.09E-02
Marine water	3.86E-05mg/L (ECETOC TRA environment v2.0)	6.44E-02
Marine sediment	2.10E-03mg/kg dry weight (ECETOC TRA environment v2.0)	2.11E-02

6.3.2. Consumer exposure: Adhesives, sealants (PC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	5.2E-9	2.17E-9
dermal	systemic	long-term	0.00284	7.96E-4
combined routes				7.96E-4

6.3.3. Consumer exposure: Adhesives, sealants (PC1)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version
1.0

Revision Date:
12.09.2019

SDS Number:
400001000051

Date of last issue: -
Date of first issue: 12.09.2019

Print Date 15.01.2020

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	9.18E-8mg/m ³	3.76E-8
dermal	systemic	long-term	0.00155mg/kg bw/day	4.34E-4
combined routes				4.34E-4

6.3.4. Consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	2.32E-8mg/m ³	9.51E-9
dermal	systemic	long-term	0.000243mg/kg bw/day	6.81E-5
combined routes				6.81E-5

6.3.5. Consumer exposure: Coatings and paints, thinners, paint removers (PC9a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	1.99E-7mg/m ³	8.16E-8
dermal	systemic	long-term	0.00615mg/kg bw/day	1.72E-3
combined routes				1.72E-3

6.3.6. Consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	2.60E-8mg/m ³	1.07E-8
dermal	systemic	long-term	7.59E-3mg/kg bw/day	2.12E-4
combined routes				2.12E-4

6.3.7. Consumer exposure: Fillers, putties, plasters, modelling clay (PC9b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	1.49E-8mg/m ³	6.11E-9
dermal	systemic	long-term	7.59E-3mg/kg bw/day	2.12E-4
combined routes				2.12E-4

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® MY 740

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	12.09.2019	400001000051	Date of first issue: 12.09.2019

Print Date 15.01.2020

6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Predicted exposures are not expected to exceed the applicable exposure limits (given in section 8 of the SDS) when the operational conditions/risk management measures given in section 2 are implemented.

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.