

TECHNICAL INFORMATION

OSIXO® AS 700 GR AEROSOL

OSIXO® AS 700 GR AEROSOL is a Perfluoropolyether (PFPE) with Polytetrafluoroethylen (PTFE) polymer in a special Solvent.

Synthetic high performance grease for rolling and plain bearing lubrication.

By bringing the active substances into a solvent, a multiplicity of application possibilities are offered. The spraying ability for example enables a minimum dosage with optimal achievement. The combination of the efficient active substances and the easy handling as well as the safe and clean application makes **OSIXO® AS 700 GR AEROSOL** an outstanding product.

OSIXO® AS 700 GR AEROSOL is solving basic problems in nearly every application such as corrosion and wear.

OSIXO® AS 700 GR AEROSOL has very good non-adhesive characteristics as well as an outstanding stability. Extremely inert, non-flammable, environmental safe, resistant against nearly all chemical substances, non-migrating, FCKW- and Silicon free. Compatible with all elastomers and polymers.

The product can be applied on a multiplicity of surfaces and is characterised by two special properties:

1. low coefficient of friction,
2. excellent separation and non-adhesive characteristic.

Application:

OSIXO® AS 700 GR AEROSOL should be applied on clean, dry and grease-free surfaces. Once applied, the coating is resistant to most solvents.

OSIXO® AS 700 GR AEROSOL can only be removed with special solvents.

Typical properties:

Useful temperature range:	-30°C to 290°C
Density @ 0°C:	1,95 g/cm ³
Density @ 20°C:	1,92 g/cm ³
Viscosity @ 40°C:	450 cSt
Appearance:	white
Odor:	odorless