

DOW CORNING

**Solar
Solutions**

Photovoltaic and Module Assembly and Integration

A Portfolio of Material Solutions from Dow Corning



Welcome to the Solar Module Assembly Product Selection Guide.

As one of the leading material houses in the world, we offer you many options across the solar value chain so that you can select the optimal solutions for your solar module and assembly operations. With material solutions tested to meet the specific requirements of the solar industry, we can help you lower costs, increase durability and improve performance.

The inherent properties of silicones—especially UV stability and ultra-transparency—provide you with numerous advantages over incumbent organics. Many of our solutions, including our breakthrough encapsulation solution, bring the advantages of superior durability, efficiency and performance and reduced manufacturing costs.

We continue to innovate new solutions to benefit our customers, building on our more than 65 years of experience in silicone chemistry—including the construction, electronics and industrial assembly industries—and more than two decades supplying the solar industry. This experience and expertise enables Dow Corning Solar Solutions to offer you the peace of mind that comes with durable, high-performing products, delivered reliably to your doorstep around the world.

We invite you to review our selection guide and contact one of our solar experts, or register for an online business account, Premier Services. Please see the back cover for more information. And if you have questions, please do not hesitate to contact us at solar.solutions@dowcorning.com. Because at the end of the day, your success is our success.

PV Rail Bond Adhesive

PV Frame Sealant

	Dow Corning® Brand	Description/Advantages	Cure System
PV Cell & Module Coating	1-2577 Low VOC Coating	<ul style="list-style-type: none"> Can be accelerated with mild heat to provide faster cure times Excellent abrasion resistance • Resists humidity and other harsh environments • Good dielectric properties • Firm, dry surface for better handling after cure • VOC exempt solvent-borne Medium viscosity 	Silicone based moisture cure
	1-2620 Low VOC Coating	<ul style="list-style-type: none"> Low viscosity version of 1-2577 coating for consumer product applications 	Silicone based moisture cure
PV Cell Encapsulant	PV-6100 Cell Encapsulant	<ul style="list-style-type: none"> Front side encapsulant • High optical transmission UV transparency down to 200 nm • Inherently UV stable Excellent humidity resistance • Fast heat cure (100°C) 	Addition cure
	PV-6120 Cell Encapsulant	<ul style="list-style-type: none"> Back side encapsulant • Opaque material enabling alternative module visual appearance • Inherently UV stable Excellent humidity resistance • Self-priming adhesion Fast heat cure (100°C) 	Addition cure
	PV-6150 Cell Encapsulant	<ul style="list-style-type: none"> Back side encapsulant • Inherently UV stable • Excellent humidity resistance • Self-priming adhesion • Fast heat cure (100°C) 	Addition cure
PV Junction Box Potting Agent	PV-7010 Potting Agent	<ul style="list-style-type: none"> Proven solution in PV industry • Fast room temperature or heat cure • Thick section cure • No solvents or cure byproducts Translucent material • Minimal shrinkage 	Addition cure
	PV-7030R Potting Agent	<ul style="list-style-type: none"> Adhesion to typical PV substrates Fast room temperature or heat cure • Thick section cure No solvents or cure byproducts • Minimal shrinkage 	Addition cure
	PV-7321 Potting Agent	<ul style="list-style-type: none"> Proven solution in PV industry • Adhesion to typical PV substrates • Good thermal conductivity 	Condensation cure
PV Junction Box Adhesive	Solar PV InstantSeal	<ul style="list-style-type: none"> Adhesion to typical PV substrates • Safe to handle—nonhazardous composition and byproducts • Clear product improves module aesthetics 	Moisture cure
	PV-804 Neutral Sealant	<ul style="list-style-type: none"> Proven solution in PV industry • Adhesion to typical PV substrates Protects against mechanical shock and thermal cycling stress at components 	Moisture cure
	PV-8007 Neutral Sealant	<ul style="list-style-type: none"> High-performance silicone adhesive/sealant with fast green strength • High elasticity after cure allows flexibility in harsh conditions • Adhesion to typical PV substrates • Protects against mechanical shock and thermal cycling stress 	Moisture cure
	PV-8101 Sealant	<ul style="list-style-type: none"> Made in China for Asia customers • Adhesion to typical PV substrates • Fast tack-free time • Flexible rubber 	Moisture cure
	PV-8101F Sealant	<ul style="list-style-type: none"> Made in China for Asia customers Adhesion to typical PV substrates • Fast tack-free time Flexible rubber • Fast deep section cure 	Moisture cure
	PV-8301 Fast Cure Sealant	<ul style="list-style-type: none"> Adhesion to typical PV substrates • Fast cure allowing increased production rates • Two-part product providing customized cure rate using <i>Dow Corning®</i> PV-8300 Base 	Condensation cure
	PV-8303 Ultra Fast Cure Sealant	<ul style="list-style-type: none"> Adhesion to typical PV substrates • Ultra fast cure for fully automated processes • Two-part product providing customized cure rate using <i>Dow Corning®</i> PV-8300 Base 	Condensation cure
	PV-8030 Adhesive	<ul style="list-style-type: none"> Adhesion to typical PV substrates • Protects against mechanical shock and thermal cycling stress at components 	Moisture cure
	PV-8080 Neutral Sealant	<ul style="list-style-type: none"> Proven technology in PV industry • Adhesion to typical PV substrates • Protects against mechanical shock and thermal cycling stress • High-performance with high elasticity after cure 	Moisture cure

Please consult the data sheets for complete information on testing methods and conditions. All products available globally except PV-8101 and PV-8101F Sealants, which are available only in Asia.

Item	Mix Ratio/ By Weight	Color	Viscosity cPs Extrusion Rate g/min	Specific Gravity Mixed Parts	Working Time @ 25°C	Cure Time/ Temperature	Thermal Conductivity	Shelf Life	UL Ratings	Packaging
Solvent Epoxy Epoxy	1-part	Clear	1050 cPs	0.88	5.5 minutes	60 minutes @ 25°C - .075 mm; 1 minute @ 60°C and 15% RH*	N/A	36 months	UL 94 V0, RTI 105°C	Bottles, cartridges, pails and drums
Solvent Epoxy Epoxy	1-part	Clear	350 cPs	0.88	5 minutes	60 minutes @ 25°C - .075 mm; 1 minute @ 60°C and 15% RH*	N/A	24 months	UL 94 V0, RTI 105°C	Cartridges, pails and drums
UV Cure	1:1; 2-part	Clear	Part A 600 cPs Part B 600 cPs	0.98	1 hour	1 minute @ 100°C	N/A	12 months	UL pending	Drums
UV Cure	1:1; 2-part	White	Part A 5300 cPs Part B 5200 cPs	1.3	1 hour	1 minute @ 100°C	0.32	12 months	UL pending	Drums
UV Cure	1:1; 2-part	Clear	Part A 440 cPs Part B 280 cPs	0.97	1 hour	1 minute @ 100°C	N/A	12 months	UL pending	Drums
UV Cure	1:1; 2-part	Trans- lucent blue and green	Part A 425 cPs Part B 400 cPs	0.98	5–10 minutes	90–100 minutes @ 25°C 10–15 minutes @ 50°C 2–5 minutes @ 75°C	0.20	12 months	UL 94 V1; UL HAI/HWI/ CTI=0; CTI/inclined plane tracking 600 V and greater; RTI 105°C; (f2)-UV/H ₂ O exposure	Cartridges, pails and drums
UV Cure	1:1; 2-part	Black	Part A 2835 cPs Part B 2733 cPs	1.2	8–10 minutes	3.25 hours @ 25°C 18.5 minutes @ 50°C 4.3 minutes @ 75°C	0.2868	12 months	UL 94 V1; HAI/CTI=0; HWI=2; CTI/inclined plane tracking 600 V and greater; RTI 105°C; Pending outdoor UV/H ₂ O	Cartridges, pails and drums
UV Cure	10:1; 2-part	White	Mixed: 8000 cPs	1.25	22 minutes	72 hours @ 25°C and 50% RH*	0.31	12 months	UL 94 HB; HAI=0; HWI=3; CTI=0; RTI 105°C	Pails and drums
UV Cure	1-part	Clear	200000 cPs	1.06	15 minutes with a green strength of 15 psi	48 hours @ 25°C - 2 mm	N/A	12 months	UL 94 HB; RTI 105°C	Pails and drums
UV Cure	1-part	White and black	190 g/minute	1.4	10–15 minutes	24 hours @ 25°C and 50% RH* - 2 mm	N/A	12 months	UL 94 HB; RTI 105°C; Outdoor UV/H ₂ O	Cartridges, pails and drums
UV Cure	1-part	White	100 g/minute	1.56	10 minutes and 50% RH*	24 hours @ 25°C and 50% RH* - 2 mm	N/A	12 months	UL 94 pending; HAI, HWI, CTI pending; RTI 105°C	Cartridges, sausages, pails and drums
UV Cure	1-part	White	320 g/minute	1.4	6 minutes and 50% RH*	24 hours @ 25°C and 50% RH* - 3 mm	N/A	12 months	UL 94 HB; HWI=2; CTI=0; RTI 105°C	Sausages and drums
UV Cure	1-part	White	210 g/minute	1.41	4 minutes and 50% RH*	24 hours @ 25°C and 50% RH* - 2 mm	N/A	12 months	UL 94 HB; HWI=2; HAI=0; CTI=0; RTI 105°C	Sausages and drums
UV Cure	10:1; 2-part	White and black	190 g/minute	1.31	20–25 minutes	8 hours @ 25°C	N/A	Catalyst black: 14 months; Catalyst clear: 12 months; Base: 14 months	UL 94 HB; HWI=3; HAI=0; CTI=0; RTI 105°C	Pails and drums
UV Cure	100 parts base to 14 parts catalyst by weight; 2-part	Black	190 g/minute	1.31	8–10 minutes	2.5 hours @ 25°C	N/A	Catalyst: 6 months Base: 14 months	UL 94 HB; HWI=2; HAI=3; CTI=0; RTI 105°C	Pails and drums
UV Cure	1-part	White	110 g/minute	1.34	20–30 minutes	24 hours @ 25°C and 50% RH* - 3 mm	N/A	18 months	UL 94 HB; RTI 105°C	Cartridges and drums
UV Cure	1-part	White and bright white	197 g/minute	1.51	10–15 minutes and 50% RH*	24 hours @ 25°C and 50% RH* - 2.5 mm	N/A	12 months	UL 94 HB; HWI=2; HAI=0; CTI=0; RTI 105°C	Cartridges, sausages, pails and drums

Conditions:
*RH: relative humidity
only in Asia.

CONVENIENT SERVICE AND SUPPORT

We know convenience and speed are extremely important to you. That's why we offer the web-based Premier Partner Network for Dow Corning Solar Solutions. You'll have easy access 24 hours a day, 7 days a week, to our full range of products for solar applications, including encapsulants, coatings, potting agents and next generation PV materials. Order on line anytime. Track orders and billing. Download critical documents. Get the information you want fast.

Premier Partner Network is the safe, convenient way to get the products and documents you need in just a few clicks—one more example of what we're doing to help you meet your goals for speed and cost-competitiveness in the rapidly developing PV market.

dowcorning.com/premier

LEARN MORE

Dow Corning has sales offices and manufacturing sites, as well as science and technology laboratories, around the globe. For more information, please visit dowcorning.com/solar or e-mail solar.solutions@dowcorning.com.

Front cover: AV11289, AV12290, AV13111, AV13896, AV12259, AV11171
Inside and back cover: AV11889

LIMITED WARRANTY INFORMATION—PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Dow Corning is a registered trademark of Dow Corning Corporation.

We help you invent the future.™ is a trademark of Dow Corning Corporation.

©2007-2011 Dow Corning Corporation. All rights reserved.

AMPM326-11

Form No. 06-1016G-01

DOW CORNING

We help you invent the future.™